


NOTE -  
 1 - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS  
 2 - SUITABLE ONLY FOR APPLICATIONS IMPARTING A RAPID STROKE TO THE SWITCH PLUNGER

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL
OPERATING FORCE ----- 4 1/2 OZ MAX	CONTACT ARRANGEMENT (SEE CIRCUIT DIAGRAM)	DO NOT SCALE PRINT
RELEASE FORCE ----- 3/4 OZ MIN	UNDERWRITERS' LAB. INC. LISTED RATING 15 A-125, 250, OR 480 VAC -L73- 1 A-125 VDC; 0.5 A-250 VDC 1/4 HP-125 VAC; 1/2 HP-250 VAC 	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
DIFFERENTIAL TRAVEL ----- .015-.075		TOLERANCES ARE:
OVERTRAVEL ----- .156 MIN		ONE PLACE (.0) ± .030 TWO PLACE (.00) ± .015 THREE PLACE (.000) ± .005 ANGLES ±
		WEIGHT

BZ-2AW82T  
 DRAWING NUMBER  
 ISSUE 8  
 RELEASE NO.  
 CHECK  
 REVISIONS  
 A CO16736  
 6 CH  
 21 DEC 62  
 B CO  
 28424  
 S R H  
 26 JAN 71  
 C CO-  
 68351-D  
 JWB  
 18 JUL 91  
 D CO-  
 75204B  
 JWB  
 1 FEB 94  
 CHECK  
 DAW 5, JAN 63  
 CHECK  
 GCH 21 DEC 62  
 DRAWN  
 FO-5037B