



NOTES

- ▲ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS
- ▲ CHARACTERISTICS MEASURED UPWARD FROM MOUNTING HOLES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE ----- 1 OZ MAX
 RELEASE FORCE ----- 1/8 OZ APPROX
 DIFFERENTIAL TRAVEL ----- .009-.060
 OVERTRAVEL ----- .266 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

-L96- 15 A - 125, 250, OR 480 VAC
 1/2 A - 125 VDC; 1/4 A - 250 VDC
 1/8 HP - 125 VAC, 1/4 HP - 250 VAC

-L288-
 -L315-
 -L306-

16A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE NOTED
 DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.015
THREE PLACE	(.000)	±.005

ANGLES
 ±.005

WEIGHT .073 LB

FORMTEK
 FO-50378
 DRAWING NUMBER
M BZ-2RW84118-A41
 PAGE 1 OF 1
 ISSUE
6
 REVISIONS

A	COI7282	LEB	4	OCT 63
B	CO-7588	K D R	29	MAK 84
C	C093346	DLT	17	SEP 98
D	0017579	KRB	08	DEC05

 CHECK
 08DEC05
 RJ
 8 OCT '63
 DAW
 CHECK
 08 DEC 05
 1 OCT 63
 CHECK
 08 DEC 05
 REPLACES
 RELEASE NO.