

# Fuseholders 1½" x ¼"

## To create a catalogue number:

Refer to the 3 columns below (terminal, body cap and panel hole type)



16A 250Vac

Examples of 7 digit catalogue numbers are given above each illustration. Then describe in words Extras.

The codes in brackets are the options illustrated. You should select the option to suit your application.

Orientation of panel locating flats and keyslots varies between body styles and terminal types.

▷ TERMINAL CODE	▷ BODY AND CAP CODE	▷ PANEL HOLE CODE	DIMENSIONS
<b>C</b>  6.3 x 0.8 Tab terminal	(C) <b>0345</b> (RA) Stock Item ⑦  ③⑥ ⑤① ③	<b>RA</b>  25 17.3 17.4 16.0/16.1	(C) <b>0345</b>  9.1 42.0 3.0 19.5
<b>D</b>  6.3 x 0.8 Tab terminal	(D) <b>0345</b> (RD)  ③⑥ ⑤①	<b>RD</b> Panel thickness between 0.8mm and 2.0mm  15.0 15.1 16.0/16.1	(D) <b>0345</b>  9.1 42.0 3.0 19.5
<b>T</b>  2.80 x 4.1 4.8 x 0.8 Solder tag	(T) <b>0347</b> (RA)  ③⑥ ⑤①	<b>RD</b> Panel thickness between 0.8mm and 4.5mm  15.0 15.1 16.0/16.1	(C) <b>0347</b>  9.1 42.0 3.0 19.5
<b>U</b>  2.80 x 4.1 4.8 x 0.8 Solder tag	(U) <b>0347</b> (RD)  ③⑥ ⑤①	<b>RD</b> Panel thickness between 0.8mm and 4.5mm  15.0 15.1 16.0/16.1	(D) <b>0347</b>  9.1 39.0 3.0 19.5

## MATERIALS and PROPERTIES

Mouldings	Nylon 6.6 (flame retardant)	Current Rating	16A* (maximum fuse rating)
Terminals	Brass, silver plated	Breakdown Voltage (d.c.)	4KV
Contacts	Copper alloy	Temperature Range	-55C - 70C (ambient)
Fixing torque	1.0Nm (8.91 lb.in) (where applicable)	Contact Resistance	3 milliohms (average)
Humidity Rating	To the req. of IEC257	Insulation Resistance	100 megohms
		Flammability rating	UL94 V2

**Terminal Cover F0873MO**  
for use with C & T terminals



\*Users should be aware of the de-rating factors published by the specialist manufacturers of fuses.

⑦ Delivery may be within seven days.