


## Fork Terminals


### Vinyl-Insulated Locking Forks — Expanded Insulation



CAT. NO.	PKG. QTY.	WIRE RANGE	MAX. INS.	BOLT HOLE	REC. TOOL	DIMENSIONS				STOCK THICK.
						A	B	C	M	
18RA-6FLX	100	22-16	.170	#6	ERG4001	.97	.25	.25	.81	.02
RA2217-170	1,000	22-16	.170	#6		.97	.25	.25	.81	
18RA-8FLX	100	22-16	.170	#8		.97	.29	.25	.81	
18RA-10FLX	100	22-16	.170	#10		.97	.29	.25	.81	
RA2257-170	1,000	22-16	.170	#10		.97	.29	.25	.81	
14RB-6FLX	100	18-14	.200	#6		.97	.31	.27	.81	.03
RB2207-200	1,000	18-14	.200	#6		.97	.31	.27	.81	
RB2217-200	1,000	18-14	.200	#6		.97	.29	.27	.81	
14RB-8FLX	100	18-14	.200	#8		.97	.31	.27	.81	
RB2237-200	1,000	18-14	.200	#8		.97	.31	.27	.81	
14RB-10FLX	100	18-14	.200	#10	.97	.31	.27	.81	.04	
RB2257-200	1,000	18-14	.200	#10	.97	.31	.27	.81		
10RC-6FLX	50	12-10	.250	#6	1.07	.31	.27	.91		
RC2207-250	500	12-10	.250	#6	1.07	.31	.27	.91		
10RC-8FLX	50	12-10	.250	#8	1.10	.37	.27	.91		
10RC-10FLX	50	12-10	.250	#10	1.10	.37	.27	.91	.04	
RC2227-250	500	12-10	.250	#10	1.10	.37	.27	.91		
10RC-14FLX	50	12-10	.250	¼"	1.22	.50	.32	.96		

For multiple wire combinations per UL File E9609, see page G-8.

### Non-Insulated Forks



CAT. NO.	PKG. QTY.	WIRE RANGE	BOLT HOLE	REC. TOOL	DIMENSIONS				STOCK THICK.
					A	B	C	M	
A18-6F	100	22-16	#6	ERG4002	.72	.25	.27	.59	.02
A116	1,000	22-16	#6		.72	.25	.27	.59	
A18-8F	100	22-16	#8		.75	.31	.27	.59	
A114	1,000	22-16	#8		.75	.31	.27	.59	
A18-10F	100	22-16	#10		.75	.31	.27	.59	
A115-TB	1,000	22-16	#10	.75	.31	.27	.59	.03	
B14-6F	100	18-14	#6	.75	.31	.27	.59		
B64	1,000	18-14	#6	.75	.31	.27	.59		
B19	1,000	18-14	#6	.66	.25	.13	.50		
B14-8F	100	18-14	#8	.75	.31	.27	.59		
B65-TB	1,000	18-14	#8	.75	.31	.27	.59	.04	
B14-10F	100	18-14	#10	.75	.31	.27	.59		
B115	1,000	18-14	#10	.75	.31	.27	.59		
B14-14F	100	18-14	¼"	.90	.44	.38	.68		
C10-6F	50	12-10	#6	ERG4005	.77	.31	.27		.63
C133	500	12-10	#6		.77	.31	.27	.63	
C10-8F	50	12-10	#8		.82	.38	.27	.63	
C114	500	12-10	#8		.82	.38	.27	.63	
C10-10F	50	12-10	#10		.82	.38	.27	.63	
C115	500	12-10	#10		.82	.38	.27	.63	
C10-14F	50	12-10	¼"		.98	.50	.37	.73	
C116-TB	500	12-10	¼"		.98	.50	.37	.73	