

KEMET Part Number: C1812C106M3PACTU
(C1812C106M3PAC7800)

SMD Comm X5R, Ceramic, 10 uF, 20%, 25 VDC, X5R, SMD, MLCC, Temperature Stable, Class II, 1812



Dimensions

| Chip Size | | 1812 |
|-----------|--|-----------------|
| L | | 4.5mm +/-0.3mm |
| W | | 3.2mm +/-0.3mm |
| T | | 1.6mm +/-0.20mm |
| B | | 0.6mm +/-0.35mm |

Packaging Specifications

| | |
|----------------------------|--------------------------|
| Packaging: | T&R, 180mm, Plastic Tape |
| Packaging Quantity: | 1000 |

General Information

| | |
|--------------------------|---|
| Series: | SMD Comm X5R |
| Style: | SMD Chip |
| Description: | SMD, MLCC, Temperature Stable, Class II |
| Features: | Temperature Stable, Class II |
| RoHS: | Yes |
| Termination: | Tin |
| Marking: | No |
| AEC-Q200: | No |
| Component Weight: | 185 mg |
| Shelf Life: | 78 Weeks |
| MSL: | 1 |

Specifications

| | |
|--|---|
| Capacitance: | 10 uF |
| Measurement Condition: | 1 kHz 1.0Vrms |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 25 VDC |
| Dielectric Withstanding Voltage: | 62.5 VDC |
| Temperature Range: | -55/+85°C |
| Temperature Coefficient: | X5R |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 15%, 1kHz 1.0Vrms |
| Dissipation Factor: | 10% 1 kHz 1.0Vrms |
| Aging Rate: | 5% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance: | 50 MOhms |