


C44P-R, Film, Metallized Polypropylene, AC Filter, 60 uF, 5%, 480 VAC, 1100 VDC



Dimensions	
D	65mm +/-0.5mm
L	147mm +/-2mm
W	18mm +/-1mm
S	28mm +/-1mm
W1	40mm +/-1mm

Packaging Specifications	
Mounting:	Bolt - M12x16
Packaging:	Bulk, Bag

General Information	
Series:	C44P-R
Dielectric:	Metallized Polypropylene
Style:	Can
Features:	Single Phase PFC
RoHS:	With Exemptions
REACH:	SVHC (Pb – CAS 7439-92-1)
SCIP Number:	cc1c1ec4-db9e-4815-b26b-e8a34ddfb776
Lead:	Threaded Studs M10
AEC-Q200:	No
Component Weight:	600 g
Miscellaneous:	Thermal Resistance = 5.9 C/W.

Specifications	
Capacitance:	60 uF
Capacitance Tolerance:	5%
Voltage AC:	480 VAC
Voltage DC:	1100 VDC
Temperature Range:	-25/+70°C
Rated Temperature:	70°C
Max dV/dt:	20 V/us
Resistance:	3.8 mOhms (10kHz)
Ripple Current:	30 Amps (10kHz 40C)
Inductance:	140 nH