

# x mate M15 Power Motor connector

## Advantages

- Very compact connector for 6 x 2,5mm<sup>2</sup>
- 4 x 630V / 16A power + 2 x 63V / 10A signal
- quick-lock system
- tamper-proof overmold evolutions
- Panel parts with M20 thread can be integrated in existing terminal boxes

# **Areas of Application**

- asynchrone induction motors up to 7,5 kW
- aggregates
- pumps





### **Technical Data**

Parameter	Standard	Value
Number of contacts		3 + 2 + PE
Wire gauge		2,5mm²
Flammability	UL 94	VO
Temperature range	IEC 60068-1	-20°C / +60°C
Mechanical operation	DIN EN 60512, test 9a	> 500 mating cycles
Rated voltage	DIN EN 60664-1 (=VDE 01 10-1)	630/63V
Rated current	DIN EN 60512-5-2, test 5b UL 1977	16A / 10A
Pollution degree	DIN EN 60664-1	3
Material group	DIN EN 60664-1	II
Installation (over voltage) category	DIN EN 60664-1	III
Rated impulse withstand voltage	DIN EN 60664-1	6000V
IP degree of protection	DIN EN 60529	IP67
Materials		
Inserts		PA
Contacts		silver plated
Description		
Receptacles		
C115 E02 041 G1	receptacle male	
C115 E05 041 G1	receptacle female	
Cable assemblies		
CA115 10 0 100 XXX	connection cable - male-female, lenghts on request	
CA115 11 0 100 XXX	male connector with cable, open end - lenghts on request	
CA115 12 0 100 XXX	female connector with cable, open end - lenghts on request	
CA115 13 0 100 XXX	male connector angled with cable, open end - lenghts on request	
CA115 14 0 100 XXX	female connector angled with cable, open end - lenghts on request	
Angled versions on request		



#### **General Information**

We reserve the right to change the design due to improvement in quality, development or production requirements. This data sheet must not be used in any form or manner without our prior approval in writing (Copyright, Law, Fair Trading Law, Civil Code). All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding; particularly the information does not constitute or provide any legal guaranties ("Beschaffenheitsgarantie" or "Haltbarkeitsgarantie")