



Main

| | |
|--------------------------------|--------------------|
| Range | TeSys |
| Product name | TeSys CAK |
| Product or component type | Control relay |
| Device short name | CA2K |
| Contactor application | Control circuit |
| Utilisation category | AC-15 DC-13 |
| Pole contact composition | 4 NO |
| [Ue] rated operational voltage | <= 690 V <= 400 Hz |
| Control circuit type | AC 50/60 Hz |
| [Uc] control circuit voltage | 24 V AC 50/60 Hz |

Complementary

| | |
|---|---|
| [Ith] conventional free air thermal current | 10 A (at 50 °C) |
| Irms rated making capacity | 110 A conforming to IEC 60947 |
| Associated fuse rating | 10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660 |
| [Ui] rated insulation voltage | 690 V conforming to IEC 60947 750 V conforming to VDE 0110 group C 690 V conforming to BS 5424 600 V conforming to CSA C22.2 No 14 |
| Mounting support | Rail Plate |
| Connections - terminals | Screw clamp terminals 1 0.00...0.01 in ² (1.5...4 mm ²)solid Screw clamp terminals 2 0.00...0.01 in ² (1.5...4 mm ²)solid Screw clamp terminals 1 cable(s) 0.75...4 mm ² flexible with cable end Screw clamp terminals 2 0.00...0.01 in ² (0.75...4 mm ²)flexible without cable end Screw clamp terminals 1 cable(s) 0.34...1.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² flexible without cable end |
| Tightening torque | 11.51 Lbf.in (1.3 N.m) screw clamp terminals flat Ø 6 mm 11.51 lbf.in (1.3 N.m) screw clamp terminals Philips No 2 0.24 in (6 mm) |
| Control circuit voltage limits | Drop-out 0.2...0.75 U _c 122 °F (50 °C)) Operational 0.8...1.15 U _c 122 °F (50 °C)) |
| Operating time | 10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing |
| Mechanical durability | 10 Mcycles |
| Maximum operating rate | 10000 cyc/h |
| Immunity to microbreaks | 2 ms |
| Inrush power in VA | 30 VA 68 °F (20 °C)) |
| Hold-in power consumption in VA | 4.5 VA 68 °F (20 °C)) |
| Heat dissipation | 1.3 W |
| Minimum switching voltage | 17 V |
| Minimum switching current | 5 mA |
| Non overlap distance | 0.02 in (0.5 mm) |
| Insulation resistance | > 10 MOhm |
| Height | 2.28 in (58 mm) |
| Maximum Width | 1.77 in (45 mm) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------|-----------------------|
| Depth | 2.24 in (57 mm) |
| Net Weight | 0.40 lb(US) (0.18 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | BS 5424 IEC 60947 NF C 63-140 VDE 0660 |
| Product certifications | CSA UL |
| IP degree of protection | IP2x |
| Protective treatment | TC IEC 60068 |
| Ambient air temperature for operation | -13...122 °F (-25...50 °C) |
| Ambient air temperature for storage | -58...176 °F (-50...80 °C) |
| Operating altitude | 6561.68 ft (2000 m) without derating |
| Flame retardance | V1 UL 94 Requirement 2 NF F 16-101 Requirement 2 NF F 16-102 |
| Mechanical robustness | Vibrations contactor open: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor closed: 4 Gn, 5...300 Hz IEC 60068-2-6 Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 |

Ordering and shipping details

| | |
|-----------------------|-------------------------|
| Category | 22371 - RELAYS, CONTROL |
| Discount Schedule | I12 |
| GTIN | 00785901903963 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.4 lb(US) (0.18 kg) |
| Returnability | Yes |
| Country of origin | ID |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.89 in (4.8 cm) |
| Package 1 width | 2.44 in (6.2 cm) |
| Package 1 Length | 2.60 in (6.6 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Weight | 20.61 lb(US) (9.35 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |

| | |
|--------------------------|--|
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|