

Pin and Sleeve Watertight Device Accessories

Closure Caps

Cap assemblies provide watertight sealing to a disconnected male IEC Pin and Sleeve plug or inlet. Manufactured out of the same tough non-metallic material as the watertight IEC Pin and Sleeve devices for corrosion and abuse resistance.

Description	Catalog Numbers
Fits all 20A 3 wire plugs and inlets.	PC320
Fits all 20A 4 wire plugs and inlets.	PC420
Fits all 20A 5 wire plugs and inlets.	PC520
Fits all 30A 3 and 4 wire plugs and inlets.	PC3430
Fits all 30A 5 wire plugs and inlets.	PC530
Fits all 60A plugs and inlets.	PC60
Fits all 100A plugs and inlets.	PC100



PC3430

Cover Assemblies

Replacement cover assemblies for use with watertight connector bodies and receptacles. Kit contains cover, arm assembly and installation tool.

Description	Catalog Numbers
Fits all 20A 3 wire watertight female devices.	CA320
Fits all 20A 4 wire watertight female devices.	CA420
Fits all 20A 5 wire watertight female devices.	CA520
Fits all 30A 3 and 4 wire watertight female devices.	CA3430
Fits all 30A 5 wire watertight female devices.	CA530
Fits all 60A watertight female devices.	CA60
Fits all 100A watertight female devices.	CA100



CA3430

Locking Ring and Cord Clamp

Replacement locking ring and cord clamp for use with IEC plug and connector.

Description	Catalog Numbers
Fits all 20A 3 wire plugs and connectors.	CC320 LR320*
Fits all 20A 4 wire plugs and connectors.	CC420 LR420*
Fits all 20A 5 wire plugs and connectors.	CC520† LR520*
Fits all 30A 3 and 4 wire plugs and connectors.	CC3430 LR3430*
Fits all 30A 5 wire plugs and connectors.	CC530† LR530*
Fits all 60A plugs and connectors.	CC60 LR60*
Fits all 100A plugs and connectors.	CC100 LR100*

* Locking Ring Only



CC3430

Liquidtight Adapters

Machined aluminum adapters are available to provide a means for attaching flexible liquidtight metal conduit to rear of a Hubbell Pin and Sleeve plug or connector. To install, remove cord grip and two gland cap screws. Use screws to attach adapter. Kellems® liquidtight conduit connectors are available to control arc of bend and to prevent conduit pull-out where vibration, motion or strain is present. These grips interface directly with Hubbell's liquidtight adapters and are available in a wide variety of N.P.T. sizes and configurations. Consult your local code grounding requirements before using liquidtight adapters.

Rating of Hubbell Pin & Sleeve Device	Liquidtight Conduit Size	Hubbell Liquidtight Adapter Cat. No.	Optional Kellems Liquidtight Conduit Grip Catalog Numbers
16 & 20 Amp	1/2" NPT	SAA12	074093402
3 & 4 Wire	3/4" NPT	SAA34	074093403
16 & 20 Amp 5 Wire	1/2" NPT	SAB12	074093402
and 30 & 32 Amp	3/4" NPT	SAB34	074093403
3 & 4 Wire	1" NPT	SAB100	074093404
30 & 32 Amp 5 Wire	3/4" NPT	SAC34	074093403
30 & 32 Amp 5 Wire	1" NPT	SAC100	074093404
and 60 & 63 Amp (all)	1 1/4" NPT	SAC125	074093405
100 & 125 Amp (all)	1 1/4" NPT	SAD125	074093405
	1 1/2" NPT	SAD150	074093406

† Consult factory

Dimensions in Inches (mm)