



CODING KEYS

APPLICATION

For those IEEE 1101.10 applications with keying requirements, but do not have front panels. IEEE 1101.10 specifications provides a method for keying slots using programming keys inserted into the front panel assembly and card guide.

Conduction Cooled Modules used in military and ruggedized systems do not use this front panel system. VITA 1.6 standard provides a method of keying for these types of systems.

FEATURES

- Complies with ANSI VITA 1.6 Standard
- Gold or Clear Chem Film aluminum bracket
- 6 configurations per coding bracket set
- 36 configurations in a 6U conduction cooled application
- Up to 1296 Keying combinations in a 6U non-conduction cooled application
- · Complimentary mounting hardware included

MATERIALS AND FINISH

CODE KEY BRACKETS

Material:

Aluminum Alloy 6061-T6 QQA-200/8

Finish:

Mil-C Class 1A, Type 1, Gold or Mil-DTL-5541 Class 3, Type II, Clear

CODE KEY PINS

Material:


Austenitic Stainless Steel

Finish:


None

WEIGHT

100 pcs. = 0.32 lbs.




VITA 1.6 CONDUCTION COOLED KEYING



The drawings above are representative of the J32 and P32 configurations. J01 and P01 are mirror images.


Samples of coding key usage




CCKP01-AD mates with CCKJ01-AD




CCKP32-ZD mates with CCKJ32-ZD



CCKP01-ZC mates with CCKJ01-ZC



CCKP32-CD mates with CCKJ32-CD



CCKP01-ZA mates with CCKJ01-ZA

CCKP32-AC mates with CCKJ32-AC

