



# Nickel Plated Brass w/ PVDF - Strain Relief Fittings PG/NPT/Metric & Elongated Threads



## PVDF Spline w/ Viton® Insert: High/Low Temperature & Chemical Resistant

Part Numbers		Cable Range	Thread Type & Size	Dimensions in Inches (mm)				
Standard	Elongated			A Clearance Hole + .01" (+.25 mm)	B Body Length	D Thread Length Standard	D Thread Length Elongated	F <sub>T</sub> /F Wrench Flats
				-31 °F to 302 °F (-35 °C to 150 °C)				
		Inches (mm)	See page 49 for thread specs					
CD07AA-RV	CD07CA-RV	.12 - .26 (3 - 6.5)	PG 7 / 1/4" NPT	.49 (12.5)	.75 (19)	.20 (5)	.39 (10)	.55 (14)
CD07AR-RV	CD07CR-RV	.08 - .20 (2 - 5)	PG 9	.60 (15.2)	.83 (21)	.24 (6)	.39 (10)	.67 (17)
CD09AA-RV	CD09CA-RV	.16 - .31 (4 - 8)						
CD09AR-RV	CD09CR-RV	.08 - .24 (2 - 6)	PG 11	.73 (18.5)	.87 (22)	.24 (6)	.39 (10)	.79 (20)
CD11AA-RV	CD11CA-RV	.20 - .39 (5 - 10)						
CD11AR-RV	CD11CR-RV	.12 - .28 (3 - 7)	PG 13 / 13.5	.80 (20.3)	.94 (24)	.26 (6.5)	.39 (10)	.87 (22)
CD13AA-RV	CD13CA-RV	.24 - .47 (6 - 12)						
CD13AR-RV	CD13CR-RV	.20 - .35 (5 - 9)	PG 16	.89 (22.5)	.91 (23)	.26 (6.5)	.39 (10)	.94 (24)
CD16AA-RV	CD16CA-RV	.39 - .55 (10 - 14)						
CD16AR-RV	CD16CR-RV	.28 - .47 (7 - 12)	PG 21	1.12 (28.4)	.94 (24)	.28 (7)	.47 (12)	1.18 (30)
CD21AA-RV	CD21CA-RV	.51 - .71 (13 - 18)						
CD21AR-RV	CD21CR-RV	.35 - .63 (9 - 16)	PG 29	1.47 (37.3)	1.14 (29)	.31 (8)	.47 (12)	1.57 (40)
CD29AA-RV	CD29CA-RV	.71 - .98 (18 - 25)						
CD29AR-RV	CD29CR-RV	.51 - .79 (13 - 20)	PG 36	1.85 (47)	1.38 (35)	.31 (8)	.59 (15)	1.97 (50)
CD36AA-RV	CD36CA-RV	.87 - 1.26 (22 - 32)						
CD36AR-RV	CD36CR-RV	.79 - 1.02 (20 - 26)	PG 42	2.13 (54.1)	1.46 (37)	.35 (9)	.59 (15)	2.24 (57)
CD42AA-RV	CD42CA-RV	1.26 - 1.50 (32 - 38)						
CD42AR-RV	CD42CR-RV	.98 - 1.22 (25 - 31)	PG 48	2.34 (59.4)	1.50 (38)	.39 (10)	.59 (15)	2.52 (64)
CD48AA-RV	CD48CA-RV	1.46 - 1.73 (37 - 44)						
CD48AR-RV	CD48CR-RV	1.14 - 1.38 (29 - 35)						
CD09NA-RV	-	.16 - .31 (4 - 8)	3/8" NPT	.68 (17.2)	.83 (21)	.59 (15)	-	.67 (17) / .75 (19)
CD09NR-RV	-	.08 - .24 (2 - 6)						
CD13NA-RV	-	.24 - .47 (6 - 12)	1/2" NPT	.83 (21.1)	.94 (24)	.51 (13)	-	.87 (22) / .94 (24)
CD13NR-RV	-	.20 - .35 (5 - 9)						
CD21NA-RV	-	.51 - .71 (13 - 18)	3/4" NPT	1.05 (26.7)	.98 (25)	.51 (13)	-	1.18 (30)
CD21NR-RV	-	.35 - .63 (9 - 16)						
CD12MA-RV	CD12DA-RV	.12 - .26 (3 - 6.5)	M12 x 1.5	.47 (12)	.75 (19)	.26 (6.5)	.39 (10)	.55 (14)
CD12MR-RV	CD12DR-RV	.08 - .20 (2 - 5)	M16 x 1.5	.63 (16)	.83 (21)	.24 (6)	.39 (10)	.67 (17) / .75 (19)
CD16MA-RV	CD16DA-RV	.16 - .31 (4 - 8)						
CD16MR-RV	CD16DR-RV	.08 - .24 (2 - 6)	M16 x 1.5	.63 (16)	.87 (22)	.24 (6)	.39 (10)	.79 (20)
CD17MA-RV	CD17DA-RV	.20 - .39 (5 - 10)						
CD17MR-RV	CD17DR-RV	.12 - .28 (3 - 7)	M20 x 1.5	.79 (20)	.91 (23)	.24 (6)	.39 (10)	.87 (22)
CD20MA-RV	CD20DA-RV	.24 - .47 (6 - 12)						
CD20MR-RV	CD20DR-RV	.20 - .35 (5 - 9)	M20 x 1.5	.79 (20)	.94 (24)	.24 (6)	.39 (10)	.94 (24)
CD22MA-RV	CD22DA-RV	.39 - .55 (10 - 14)						
CD22MR-RV	CD22DR-RV	.28 - .47 (7 - 12)	M25 x 1.5	.98 (25)	1.02 (26)	.28 (7)	.47 (12)	1.18 (30)
CD25MA-RV	CD25DA-RV	.51 - .71 (13 - 18)						
CD25MR-RV	CD25DR-RV	.35 - .63 (9 - 16)	M32 x 1.5	1.26 (32)	1.22 (31)	.31 (8)	.47 (12)	1.57 (40)
CD32MA-RV	CD32DA-RV	.71 - .98 (18 - 25)						
CD32MR-RV	CD32DR-RV	.51 - .79 (13 - 20)	M40 x 1.5	1.57 (40)	1.46 (37)	.31 (8)	.59 (15)	1.97 (50)
CD40MA-RV	CD40DA-RV	.87 - 1.26 (22 - 32)						
CD40MR-RV	CD40DR-RV	.79 - 1.02 (20 - 26)						



Suggested Clearance Hole for Non-Threaded Mounting



Viton® is a federally registered trademark of DuPont Dow Elastomer.

\*Note: VDE Approval only applies to Fittings with Metric Thread.

Dome Fittings also available with the following approvals:



### Typical Application:

- High Performance
- Extreme Temperatures
- Sturdy

