

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click  to remove) [Search Tips](#)

 **Text Search: 'CD9-4A'**


Your search criteria matched only one product, shown below

CD9-4A



Reel Smart™ Installation Requirements.

All tooling information, including crimp shut height dimension, is included on the product reel label.

Part Number	CD9-4A
RoHS Compliancy Status	RoHS directive is not applicable
Part Description	Die Insert for CA9 Applicator
60/40 Solder Slug Dia. (In.)	.188
60/40 Solder Slug Dia. (mm)	4.78
CE Compliant	No
CE Marking	No
Panduit Color Code	Red
Pricing Description	Die Insert, for use with CA9 Applicator, to terminate PANDUIT reeled disconnects
Wire Insulation Strain Relief	Insulation Support
Wire Range	22 – 18
Wire Range (mm ²)	0.5 – 1.0
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.