



(2.54 mm) .100"

SLW, CES SERIES

LOW-PROFILE SOCKET STRIPS

SLW Mates with:
TLW, TSW, MTLW, MTSW,
HW, EW, ZW, HTSW,
HMTSW, TSM

CES Mates with:
TLW, TSW, MTLW,
MTSW, HW, EW, ZW,
DW, HTSW, PHT, HMTSW

SPECIFICATIONS

For complete specifications see www.samtec.com?SLW or www.samtec.com?CES

Insulator Material:
Black G.F. Polyester
Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 μ" (1.27 μm) Ni
SLW Current Rating (SLW/TSW):
5.2 A per pin
(2 pins powered)
CES Current Rating (TSW/CES):
5.5 A per pin
(2 pins powered)
Voltage Rating:
SLW: 406 VAC
CES: 400 VAC
Operating Temp Range:
-55 °C to +125 °C with Gold
-55 °C to +105 °C with Tin
Insertion Depth:
SLW: (2.16 mm) .085" to
(2.92 mm) .115"
CES: (2.62 mm) .103" to
(4.06 mm) .160"
RoHS Compliant:
Yes
Lead-Free Solderable:
No, Lead Wave only

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- Other platings
- Contact Samtec.

Note:
Some lengths, styles and options are non-standard, non-returnable.

SLW	1	NO. PINS PER ROW	01	PLATING OPTION	ROW OPTION								
01 thru 50													
<table border="0"> <tr> <td>-F = Gold flash on contact, Matte Tin on tail</td> <td>-S = Single Row</td> </tr> <tr> <td>-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail</td> <td>-D = Double Row</td> </tr> <tr> <td>-G = 20 μ" (0.51 μm) Gold on contact, Gold flash on balance</td> <td></td> </tr> <tr> <td>-T = Matte Tin</td> <td></td> </tr> </table>						-F = Gold flash on contact, Matte Tin on tail	-S = Single Row	-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail	-D = Double Row	-G = 20 μ" (0.51 μm) Gold on contact, Gold flash on balance		-T = Matte Tin	
-F = Gold flash on contact, Matte Tin on tail	-S = Single Row												
-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail	-D = Double Row												
-G = 20 μ" (0.51 μm) Gold on contact, Gold flash on balance													
-T = Matte Tin													

CES	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	RA OPTION								
01 thru 50														
<table border="0"> <tr> <td>-01 = (3.25 mm) .128 "A" Dim.</td> <td>-L = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail</td> <td>-S = Single Row</td> <td>-RA = Right-angle version</td> </tr> <tr> <td>-02 = (5.66 mm) .223 "A" Dim.</td> <td>-T = Matte Tin</td> <td>-D = Double Row</td> <td>Style -02 only Single Row only</td> </tr> </table>							-01 = (3.25 mm) .128 "A" Dim.	-L = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail	-S = Single Row	-RA = Right-angle version	-02 = (5.66 mm) .223 "A" Dim.	-T = Matte Tin	-D = Double Row	Style -02 only Single Row only
-01 = (3.25 mm) .128 "A" Dim.	-L = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail	-S = Single Row	-RA = Right-angle version											
-02 = (5.66 mm) .223 "A" Dim.	-T = Matte Tin	-D = Double Row	Style -02 only Single Row only											

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.