


CABLE ENTRY SEALS



✓ Active

TE CONNECTIVITY (TE)

CES-3R

Raychem | CS

CES-3R

TE Internal Number: CC4331-000

EU RoHS Compliant EU ELV Compliant

Seal Type Standard

Material Nylon, Polyolefin

Number of Branches/Legs 1

Expanded Inside Diameter (Min) 28 mm [1.1 in]

Recovered Inside Diameter (Max) 10 mm [.394 in]



PRODUCT DRAWING

DOCUMENTATION

Product Drawings

Cable Entry Seals, Right Angle, Standard

PDF

English

Product Specifications

Product Specification

Thermofit Polyolefin Molded Components Flame-Retarded, Semi-Rigid, Heat-Shrinkable

PDF

English

Raychem \$1297 And /97 Hot Melt Adhesive

PDF

English

FEATURES	+
Please review product documents or contact us for the latest agency approval information.	
Please Note: Use the Product Drawing for all design activity.	
Product Type Features	
Thread Size 1-3/8-12	
Product Type Heat Shrink Cable Entry Seal Angle 90°	
Configuration Features	
Number of Branches/Legs 1	
Body Features	
Seal Type Standard Material Nylon, Polyolefin	
Dimensions	
Expanded Inside Diameter (Min) 28 mm [1.1 in]	
Recovered Inside Diameter (Max) 10 mm [.394 in] Drill Size 1.375	
Cable Diameter Range 10.16 – 23.88 mm [.4 – .94 in]	
Overall Length (Recovered) 53 mm [2.1 in]	
Overall Length (Supplied) 53 mm [2.1 in]	
Usage Conditions	
Flammability Flame-Retardant	
Other	
Comment Molded part has hot-melt adhesive preinstalled.	
PRODUCT COMPLIANCE	+
Statement of Compliance	
Statement of Compliance	
PDF	