

PIN & SLEEVE ORDERING INFORMATION*

20A AND 30A NORTH AMERICAN RATINGS SERIES 2 16A AND 32A INTERNATIONAL RATINGS SERIES 1					WATERTIGHT DEVICES							
Amps	Wires and Poles	CONFIGURATION		Voltage	Straight Receptacle	Angled 15° Receptacle†	Plug	Connector	Inlet	Interlock Unfused	Circuit Breaker Interlock	
		Recept./Conn.	Plug/Inlet									
16A	2W3P			110-130	CH316R4W	CH316RA4W	CH316P4W	CH316C4W	CH316B4W	CH316MI4W	CH316MIB4W	
	2W3P			220-240	CH316R6W	CH316RA6W	CH316P6W	CH316C6W	CH316B6W	CH316MI6W	CH316MIB6W	
	3W4P			380-400	CH416R6W	CH416RA6W	CH416P6W	CH416C6W	CH416B6W	CH416MI6W	CH416MIB6W	
	4W5P			220-380 & 240-415	CH516R6W	CH516RA6W	CH516P6W	CH516C6W	CH516B6W	CH516MI6W	CH516MIB6W	
20A	2W3P			125	CH320R4W	CH320RA4W	CH320P4W	CH320C4W	CH320B4W	CH320MI4W	CH320MIB4W	
	2W3P			250	CH320R6W	CH320RA6W	CH320P6W	CH320C6W	CH320B6W	CH320MI6W	CH320MIB6W	
	2W3P			480	CH320R7W	CH320RA7W	CH320P7W	CH320C7W	CH320B7W	CH320MI7W	CH320MIB7W	
	3W4P			125/250	CH420R12W	CH420RA12W	CH420P12W	CH420C12W	CH420B12W	CH420MI12W	CH420MIB12W	
	3W4P			3Ø250	CH420R9W	CH420RA9W	CH420P9W	CH420C9W	CH420B9W	CH420MI9W	CH420MIB9W	
	3W4P			3Ø480	CH420R7W	CH420RA7W	CH420P7W	CH420C7W	CH420B7W	CH420MI7W	CH420MIB7W	
	3W4P			3Ø600	CH420R5W	CH420RA5W	CH420P5W	CH420C5W	CH420B5W	CH420MI5W	CH420MIB5W	
	4W5P			3ØY120/208	CH520R9W	CH520RA9W	CH520P9W	CH520C9W	CH520B9W	CH520MI9W	CH520MIB9W	
	4W5P			3ØY277/480	CH520R7W	CH520RA7W	CH520P7W	CH520C7W	CH520B7W	CH520MI7W	CH520MIB7W	
	4W5P			3ØY347/600	CH520R5W	CH520RA5W	CH520P5W	CH520C5W	CH520B5W	CH520MI5W	CH520MIB5W	
	30A	2W3P			125	CH330R4W	CH330RA4W	CH330P4W	CH330C4W	CH330B4W	CH330MI4W	CH330MIB4W
		2W3P			250	CH330R6W	CH330RA6W	CH330P6W	CH330C6W	CH330B6W	CH330MI6W	CH330MIB6W
2W3P				480	CH330R7W	CH330RA7W	CH330P7W	CH330C7W	CH330B7W	CH330MI7W	CH330MIB7W	
3W4P				125/250	CH430R12W	CH430RA12W	CH430P12W	CH430C12W	CH430B12W	CH430MI12W	CH430MIB12W	
3W4P				3Ø250	CH430R9W	CH430RA9W	CH430P9W	CH430C9W	CH430B9W	CH430MI9W	CH430MIB9W	
3W4P				3Ø480	CH430R7W	CH430RA7W	CH430P7W	CH430C7W	CH430B7W	CH430MI7W	CH430MIB7W	
3W4P				3Ø600	CH430R5W	CH430RA5W	CH430P5W	CH430C5W	CH430B5W	CH430MI5W	CH430MIB5W	
4W5P				3ØY120/208	CH530R9W	CH530RA9W	CH530P9W	CH530C9W	CH530B9W	CH530MI9W	CH530MIB9W	
4W5P				3ØY277/480	CH530R7W	CH530RA7W	CH530P7W	CH530C7W	CH530B7W	CH530MI7W	CH530MIB7W	
4W5P				3ØY347/600	CH530R5W	CH530RA5W	CH530P5W	CH530C5W	CH530B5W	CH530MI5W	CH530MIB5W	
32A		2W3P			110-130	CH332R4W	CH332RA4W	CH332P4W	CH332C4W	CH332B4W	CH332MI4W	CH332MIB4W
		2W3P			220-240	CH332R6W	CH332RA6W	CH332P6W	CH332C6W	CH332B6W	CH332MI6W	CH332MIB6W
	3W4P			380-400	CH432R6W	—	CH432P6W	CH432C6W	CH432B6W	CH432MI6W	CH432MIB6W	
	4W5P			220-380 & 240-415	CH532R6W	CH532RA6W	CH532P6W	CH532C6W	CH532B6W	CH532MI6W	CH532MIB6W	

* Splashproof IP44 products are also available—please consult factory.

250VDC and Barge Overflow products are also available—please consult factory.

† Angled 80° receptacles are also available. To order, add suffix "80" directly after "RA" in the angled 15° receptacle catalog number. Example: CH330RA804W

Ordering Information

PIN & SLEEVE ORDERING INFORMATION*

**60A AND 100A
NORTH AMERICAN RATINGS SERIES 2
63A AND 125A
INTERNATIONAL RATINGS SERIES 1**

WATERTIGHT DEVICES



Straight Receptacle

Angled 15° Receptacle†

Plug

Connector

Inlet

Interlock Unfused

Circuit Breaker Interlock

Amps	Wires and Poles	CONFIGURATION		Voltage	WATERTIGHT DEVICES						
		Recept./ Conn.	Plug/Inlet		Straight Receptacle	Angled 15° Receptacle†	Plug	Connector	Inlet	Interlock Unfused	Circuit Breaker Interlock
60A	2W3P			125	CH360R4W	CH360RA4W	CH360P4W	CH360C4W	CH360B4W	CH360MI4W	CH360MIB4W
	2W3P			250	CH360R6W	CH360RA6W	CH320P6W	CH360C6W	CH360B6W	CH360MI6W	CH360MIB6W
	2W3P			480	CH360R7W	CH360RA7W	CH360P7W	CH360C7W	CH360B7W	CH360MI7W	CH360MIB7W
	3W4P			125/250	CH460R12W	CH460RA12W	CH460P12W	CH460C12W	CH460B12W	CH460MI12W	CH460MIB12W
	3W4P			3Ø250	CH460R9W	CH460RA9W	CH460P9W	CH460C9W	CH460B9W	CH460MI9W	CH460MIB9W
	3W4P			3Ø480	CH460R7W	CH460RA7W	CH460P7W	CH460C7W	CH460B7W	CH460MI7W	CH460MIB7W
	3W4P			3Ø600	CH460R5W	CH460RA5W	CH460P5W	CH460C5W	CH460B5W	CH460MI5W	CH460MIB5W
	4W5P			3ØY120/208	CH560R9W	CH560RA9W	CH560P9W	CH560C9W	CH560B9W	CH560MI9W	CH560MIB9W
	4W5P			3ØY277/480	CH560R7W	CH560RA7W	CH560P7W	CH560C7W	CH560B7W	CH560MI7W	CH560MIB7W
	4W5P			3ØY347/600	CH560R5W	CH560RA5W	CH560P5W	CH560C5W	CH560B5W	CH560MI5W	CH560MIB5W
63A	2W3P			220-240	CH363R6W	CH363RA6W	CH363P6W	CH363C6W	CH363B6W	CH363MI6W	CH363MIB6W
	3W4P			380-400	CH463R6W	CH463RA6W	CH463P6W	CH463C6W	CH463B6W	CH463MI6W	CH463MIB6W
	4W5P			220-380 & 240-415	CH563R6W	CH563RA6W	CH563P6W	CH563C6W	CH563B6W	CH563MI6W	CH563MIB6W
100A	2W3P			125	CH3100R4W	CH3100RA4W	CH3100P4W	CH3100C4W	CH3100B4W ‡	CH3100MI4W	CH3100MIB4W
	2W3P			250	CH3100R6W	CH3100RA6W	CH3100P6W	CH3100C6W	CH3100B6W ‡	CH3100MI6W	CH3100MIB6W
	2W3P			480	CH3100R7W	CH3100RA7W	CH3100P7W	CH3100C7W	CH3100B7W ‡	CH3100MI7W	CH3100MIB7W
	3W4P			125/250	CH4100R12W	CH4100RA12W	CH4100P12W	CH4100C12W	CH4100B12W ‡	CH4100MI12W	CH4100MIB12W
	3W4P			3Ø250	CH4100R9W	CH4100RA9W	CH4100P9W	CH4100C9W	CH4100B9W ‡	CH4100MI9W	CH4100MIB9W
	3W4P			3Ø480	CH4100R7W	CH4100RA7W	CH4100P7W	CH4100C7W	CH4100B7W ‡	CH4100MI7W	CH4100MIB7W
	3W4P			3Ø600	CH4100R5W	CH4100RA5W	CH4100P5W	CH4100C5W	CH4100B5W ‡	CH4100MI5W	-
	4W5P			3ØY120/208	CH5100R9W	CH5100RA9W	CH5100P9W	CH5100C9W	CH5100B9W ‡	CH5100MI9W	CH5100MIB9W
	4W5P			3ØY277/480	CH5100R7W	CH5100RA7W	CH5100P7W	CH5100C7W	CH5100B7W ‡	CH5100MI7W	CH5100MIB7W
	4W5P			3ØY347/600	CH5100R5W	CH5100RA5W	CH5100P5W	CH5100C5W	CH5100B5W ‡	CH5100MI5W	-
125A	2W3P			110-130	CH3125R6W	CH3125RA6W	CH3125P6W	CH3125C6W	CH3125B6W ‡	CH3125MI6W	CH3125MIB6W
	3W4P			380-400	CH4125R6W	CH4125RA6W	CH4125P6W	CH4125C6W	CH4125B6W ‡	CH4125MI6W	CH4125MIB6W
	3W4P			500	CH4125R7W	CH4125RA7W	CH4125P7W	CH4125C7W	CH4125B7W ‡	CH4125MI7W	-
	4W5P			220-380 & 240-415	CH5125R6W	CH5125RA6W	CH5125P6W	CH5125C6W	CH5125B6W ‡	CH5125MI6W	CH5125MIB6W

* Splashproof IP44 products are also available—please consult factory.

250VDC and Barge Overflow products are also available—please consult factory.

† Angled 80° receptacles are also available. To order, add suffix "80" directly after "RA" in the angled 15° receptacle catalog number. Example: CH330RA804W

‡ 100A and 125A inlets are straight.