

# Sumitomo 4 Way Hinged Interface

Straight and 90° elbow interfaces providing high integrity connections between Sumitomo connectors and Harnessflex conduit systems. These interfaces are designed to snap together over all types of Harnessflex slit and unslit conduit, maintaining maximum conduit bore. In addition, 90° elbow versions allow the conduit to swivel 360° around the connector housing.



\*Image is representative of finished product, details may vary

- One-piece external design for unrestricted bore and quick assembly with no tools.
- High pull-off strength - conduit corrugations sit tightly into joiner junctions.
- Conduit size labels - each junction indicates nominal conduit size to aid installation
- Polyamide (Nylon) 66
- IP40 rated
- Temperature Range: -40°C to +120°C
- Very high UV resistance
- Self extinguishing, low smoke toxicity & halogen free

## Conformity

- CE Mark to the low voltage directive
- RoHS Compliant to 2011/65/EU
- Conforms with end of life vehicle directive (ELV) EU200/53/EC

[Parts list](#)

[Documents](#)

[Related products](#)

[Contact us](#)

Part No.	Conduit Size		Interface Reference	Connector Reference
	NC	NW		
CI08-SU4	08	7.5	--	--
CI08-90-SU4	08	8.5	--	--

### POPULAR LINKS

- [ABB Connect](#)
- [ABB Electrification](#)
- [Where to buy](#)
- [Mission to Zero](#)
- [ABB Ability](#)
- [Supplying to ABB](#)

### FOLLOW US



### EVENTS

- [Customer events](#)
- [Investor events](#)
- [Media events](#)

### CURRENT SHARE PRICE

New York

**35.03** USD

-0.40% at 2021-06-08, 16:00