



Thin-Wall Heat-Shrinkable Tubing

T&B Catalog Number: CPO187-0-25
UPC Number: 78621085113
Status: Active

Description:

Thin-Wall Heat-Shrinkable Tubing for Cable Range 22 - 14 AWG, Expanded Dia. 3/16, Length 25 feet reel, rated for 600V, 125 degrees C, Material: Cross-linked polyolefin - Non-lined, Black



Where To Buy

Enter Zip Code:

Enter Quantity:

Features

- Flame-retardant, cross-linked polyolefin.
- Meets UL 224, 125°C; CSA 22.2 No. 198.1, 125°C; MIL-DTL-23053/5 Class 1&2; AMS 3636 & 3637; DEF STAN 59-97, Issue 3, Type 2a

General

Style	CPO Series Non-Lined
Color	Black
Temperature Range	-55°C - 135°C
Shrink Ratio	2:1

Dimension Information

Length (feet)	25
Minimum Expanded I.D. (inches)	0.187
Maximum Recovered I.D. (inches)	0.093
Nominal Recovered Wall (inches)	0.02
Cable Range	22 - 14 AWG

Specifications

Shrink Temperature	120°C
--------------------	-------

Packaging

Order Multiple	1
Inner Package	1
Outer Package	10
Package Height	13
Package Length	13
Package Width	6
T&B Sold in UOM	Each
T&B Weight Per UOM	26 lbs. per 100

Application Support

MSDS Number	MSDS-0020-TB2
Specifications	Click Here
Overview	Click Here

Notes

- Order multiple is for 4 ft. sticks is 25 sticks. Order multiple for reels is 1 reel. When ordering standard package, order by package not feet.
- UL Recognized File Number E137759 and CSA Certified. Clear material not UL Recognized.
- Larger diameters available upon special request; consult Customer Service.

Certifications

RoHS Compliance Yes [Generate Compliance Certificate](#)

Certifications

