



**Cable to Ground Rod
T&B Catalog Number:**

CR2-4-6251/0

UPC Number:

78378614490

Status:

Active

Description:

Exothermic Welding reusable graphite mold for Cable to Ground Rod Connection. Type CR2 - Splice Conductors to Top of Rod, 1/0 AWG Wire Size to Rod 5/8" Nominal Diameter, Actual Shank Dia. 0.560" , 90RTB Welding Powder Size, Hand

General

Function	Splice Conductors to Top of Rod
Rod Size (A) (inches)	5/8" Nominal Diameter, Actual Shank Dia. 0.560"
Wire Size (B)	1/0 AWG
Welding Powder Size	90RTB
Handle Clamp Type	HCPK4
Sleeve	-

Specifications

Specification Guide	Available on Website
---------------------	----------------------

Packaging

T&B Order Multiple	1
Package in Units	1
Std. Ctn	1
T&B Sold in UOM	Each
T&B Weight Per UOM	3.4 lbs. Each

Application Support

Furseweld Overview	Available on Website
Furseweld Cross Reference	Available on Website
Additional Tables	Available on Website

Notes

For Connections to Extensible (Threaded) Rods -
Remove Top Threaded Section

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com