

Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Tool for processing ferrules according to DIN 46228-4, 0.5 mm² to 2.5 mm², equipped with pressure lock, cutting, stripping, twisting, and crimping unit, with three magazines including a strip each of ferrules from 0.5 mm² ... 2.5 mm², packaged in a robust plastic case

Why buy this product

- ✓ Integrated pressure lock ensures consistently high-quality crimping
- ✓ Up to 30% time savings since the process steps required for assembling conductors can be carried out using only one tool
- ✓ Multifunctional crimping pliers for the processing of Taped ferrules according to DIN 46228-4
- ✓ Robust and durable due to use of resistant plastics and annealed metals
- ✓ Visualized process flows directly on the pliers simplify operation



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 055626 042398 |
| GTIN | 4055626042398 |
| Weight per Piece (excluding packing) | 720.000 g |
| Custom tariff number | 82032000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------|---------|
| Length (b) | 180 mm |
| Width (a) | 31.5 mm |

Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

Technical data

Dimensions

| | |
|--------|--------|
| Height | 100 mm |
|--------|--------|

General

| | |
|----------------------------------|---------------------|
| Compression | Indent crimp |
| Type of contact | Ferrules |
| Min. AWG, flexible, multi-strand | 14 |
| AWG max., flexible, multi-strand | 20 |
| Min. cross section | 0.5 mm ² |
| Max. cross section | 2.5 mm ² |
| AWG min | 20 |
| AWG max | 14 |
| Maximum stripping length | 11 mm |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 8.0 | 21043811 |
| eCl@ss 9.0 | 21043811 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000168 |
| ETIM 5.0 | EC000168 |
| ETIM 6.0 | EC000168 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 27111518 |
|-------------|----------|

Accessories

Accessories

Connector

Ferrule - Al 0,5-8 WH S1 - 1200104



Taped ferrules, 0.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, white, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

Accessories

Ferrule - AI 0,75- 8 GY S1 - 1200105



Taped ferrules, 0.75 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, gray, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - AI 1,0-8 RD S1 - 1200106



Taped ferrules, 1.0 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, red, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - AI 1,5-8 BK S1 - 1200107



Taped ferrules, 1.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, black, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - AI 2,5-8 BU S1 - 1200108



Taped ferrules, 2.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, blue, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 40 sleeves per strip.

Ferrule - AI 0,75- 8 BU S1 - 1200163



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, Sleeve length: 8 mm, Length: 14 mm, Color: blue, Number of strips: 10, Number of sleeves per strip: 50

Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

Accessories

Ferrule - Al 2,5-8 GY S1 - 1200164



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, Sleeve length: 8 mm, Length: 14 mm, Color: gray, Number of strips: 10, Number of sleeves per strip: 40

Magazine

Magazine - CRIMPFOX 4 IN 1/MAG - 1200103



Ferrule magazine for CRIMPFOX 4 IN 1, for ferrules with insulating collars from 0.5 mm² ... 2.5 mm², with a length of 8 mm