

## Honeywell Sensing and Control

Search



### narrow your search

#### Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6165)
- Switches (9781)
- Wireless (45)

#### Technology

- Control and Instrumentation (890)
- Electromechanical (9307)
- Magnetic (541)
- Platinum thin film (56)
- Thick Film (1372)
- More...

### new products

#### New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



[Wireless Web Site WGLA and WPMM XYR6000™](#)

[find out more](#)

### white papers

- [Wireless Switches Offer Unlimited Benefit](#)
- [Basic Switches Are Not Created Equal](#)
- [Applying Precision Switches](#)
- [Sensors for Medical Devices](#)
- [New Ways to Measure Torque](#)
- [Choosing Safety Switches](#)
- [Specifying Hour Meters](#)

### Need help?

[Click here to contact us](#)

**CSNE151-002**  
( Home : Products : Sensors » Current Sensors » Closed Loop » CSN )



Actual product appearance may vary.

CSN Series closed loop current sensor, measures ac, dc or impulse current, 25 amp-turns nominal, ±43 amp-turns range, high temperature, potted, 1000 turn

[Sales & Service](#) [Distributor Inventory](#)

[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

#### Product Specifications

Product Type	Closed Loop Linear
Sensed Current Type	ac or dc
Sensed Current Range	±43 A
Package Type	Series Connect PCB Mount
Output Type	Current
Continuous Current	±36 A
Operate Current	25 A RMS @ 25 °C
Supply Current	±10 mA + Output
Supply Voltage	±15.0 Vdc
Offset Current	< ±0.15 mA
Offset Current Drift	< ±0.6 mA
Coil Resistance	110 Ohm
Response Time	< 1 µs
Coil Turns	1000
Output Nominal	25 mA
Operating Temperature	-40 °C to 85 °C [-40 °F to 185 °F]
Storage Temperature	-40 °C to 90 °C [-40 °F to 194 °F]
Measuring Resistance	100 Ohm min., 320 Ohm max.
Housing Material	Glass-filled PBT (UL94-V0)
Mounting	PCB on 17 Pins
Pinout Style	7 Pin
Accuracy	±0.5 %
Availability	Global
Comment	Extended operating temperature range and seven integral primary turns. Sensed current range only applies up to 70 °C.
UNSPSC Code	411121
UNSPSC Commodity	411121 Transducers
Series Name	CSN

### contacts

- [Customer Service](#)
- [Technical Support](#)
- [Global Sales & Service](#)
- [View Site Demo](#)
- [Site Comments?](#)

### meet dr. larry

**VIDEO** - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

### my links

- [Login to iCOM](#)
- [Login to Rep/AD Portal](#)
- [Login to Digital University](#)

### News Center

Honeywell Introduces TruStability® NSC Series, Uncompensated / Unamplified Board Mount Pressure Sensors

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL INTRODUCES ITS HAWK™ RESOLVERS 1-INCH SERIES, FULLY HOUSED CONFIGURATION

HONEYWELL INTRODUCES MICROPOWER OMNIPOLAR DIGITAL HALL-EFFECT SENSOR ICS WITH LOW SUPPLY VOLTAGE AND ULTRA LOW TYPICAL CURRENT

HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

HONEYWELL ADDS NEW 100° AND 180° ARC CONFIGURATIONS TO ITS SMART POSITION SENSOR PORTFOLIO

[MICRO SWITCH Anniversary site](#)