


**Product Families**

- ▶ Automation
- ▶ Hazardous Location
- ▶ Industrial Components
- ▶ LED Lighting & Signaling
- ▶ Machine Safety
- ▶ Sensing

**CW1L-A1E20QHS**  
CW ILLD PB Blue



Add to Cart

**Key Features**

- ø22.3mm mounting hole compliant with IEC 60947-5-1
- 3.5-mm operator travel for pushbuttons ensures comfortable and reliable operation
- Black and metallic bezels available
- Illuminated pushbuttons, pushbuttons, pilot lights, selector switches and key selector switches are available
- Direct opening NC contact
- 10A contact rating; up to three contact blocks for non-illuminated and two contact blocks for illuminated models can be connected
- Up to 6 contacts per switch
- UL Type 4X rating



**Specifications**

Literature

Downloads

<b>Product Type</b>	Illuminated Pushbutton
<b>Mounting Hole Size</b>	22mm
<b>Shape</b>	Round
<b>Color</b>	Blue
<b>Contact Rating</b>	10A
<b>Normally Open Contacts</b>	2
<b>Normally Closed Contacts</b>	0
<b>Ingress Protection Rating</b>	IP65 degree of protection (IEC 60529) from panel front
<b>Operation Type</b>	Maintained