



[Sign In/Register](#)

[HOME](#) [PRODUCTS](#) [SUPPORT](#) [ABOUT US](#) [NEWS](#) [CONTACT](#)

[SEARCH](#)

[HOME](#) [Industrial Components](#) [Switches & Pilot Devices](#) [CW Series](#) [CW4B-M1E20W](#)

**Product Families**

- Automation**
- Hazardous Location**
- Industrial Components**
- LED Lighting & Signaling**
- Machine Safety**
- Sensing**

## CW4B-M1E20W Pushbutton 22MM 2NO White



### Key Features

- ø22.3mm mounting hole compliant with IEC 60947-5-1
- 3.5-mm operator travel for pushbuttons ensures comfortable and reliable operation
- Black and metallic bezels available
- Illuminated pushbuttons, pushbuttons, pilot lights, selector switches and key selector switches are available
- Direct opening NC contact
- 10A contact rating; up to three contact blocks for non-illuminated and two contact blocks for illuminated models can be connected
- Up to 6 contacts per switch
- UL Type 4X rating



[Specifications](#) [Literature Downloads](#)

<b>Product Type</b>	Pushbutton
<b>Mounting Hole Size</b>	22mm
<b>Shape</b>	Round
<b>Color</b>	White
<b>Contact Rating</b>	10A
<b>Normally Open Contacts</b>	2
<b>Normally Closed Contacts</b>	0
<b>Ingress Protection Rating</b>	IP65 degree of protection (IEC 60529) from panel front
<b>Operation Type</b>	Momentary