


Product Families

- ▶ Automation
- ▶ Hazardous Location
- ▶ Industrial Components
- ▶ LED Lighting & Signaling
- ▶ Machine Safety
- ▶ Sensing

CW4L-M2E10Q4G
Illuminated PB 22MM 1NO G

Add to Cart



Key Features

- ø22.3mm mounting hole compliant with IEC 60947-5-1
- 3.5-mm operator travel for pushbuttons ensures comfortable and reliable operation
- Black and metallic bezels available
- Illuminated pushbuttons, pushbuttons, pilot lights, selector switches and key selector switches are available
- Direct opening NC contact
- 10A contact rating; up to three contact blocks for non-illuminated and two contact blocks for illuminated models can be connected
- Up to 6 contacts per switch
- UL Type 4X rating



Specifications Literature Downloads

| | |
|----------------------------------|--|
| Product Type | Illuminated Pushbutton |
| Mounting Hole Size | 22mm |
| Shape | Round |
| Color | Green |
| Contact Rating | 10A |
| Normally Open Contacts | 1 |
| Normally Closed Contacts | 0 |
| Ingress Protection Rating | IP65 degree of protection (IEC 60529) from panel front |
| Illumination Voltage | 24VAC/DC |
| Lamp Type | LED |
| Operation Type | Momentary |