

Part number
CX 02 7F



Brief description:

female insert, 2 poles, crimp connections, 70A 1000V, 8kV, 3, 2 modules, modular units series MIXO

Product description

Model	female insert
Version	Crimp connection
Product type	for 70A female contacts
Family	MIXO series, customizable inserts
Size	1 module
N. of poles	2 poles


Technical data

Current	70 A (A.C. and D.C.)
Voltage	1000 V
Rated impulse withstand voltage	8 kV
Pollution degree	3
Operating temperature range (min, max)	-40°C ... +125°C
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

Further technical details

Characteristics according to EN 61984	70A 1000V 8kV 3; 70A 1600V 12kV 2
Insulation resistance	≥ 10 GΩ
Rated voltage according to UL/CSA	600V
UL 94 flammability rating	V-0
Weight	10,00 g

Approvals / Standards

Reference standard	EN 61984:2009-06
Quality mark	 DNV GL, BV, EAC
Conformity	CQC, CE

General ordering information

EAN13 code	8015747182454
Tariff number	85369095

Packaging Information

Packaging length	180,00 mm
Packaging height	130,00 mm
Packaging width	150,00 mm
Packaging weight	0,78 kg
Packaging volume	3,51 dm ³
Packaging description	Carton box
Packaging quantity	60 Pcs
Packaging EAN code	8015747221146
Sub-packaging length	35,00 mm
Sub-packaging height	40,00 mm
Sub-packaging width	155,00 mm
Sub-packaging weight	0,13 kg
Sub-packaging volume	0,22 dm ³
Sub-packaging description	Carton tray
Sub-packaging quantity	10 Pcs
Sub-packaging EAN barcode	8015747182522

Part number

CX 02 7F



Notes

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support
