

[Skip to content](#)

[Corporate Home](#) | [Electronic Components](#) | [Segments](#) | [Who We Are](#)

Worldwide



Our commitment. Your advantage.

Search

By:



[Sign In](#) | [Register \(Why Register?\)](#)

[Products](#)



- Connectors
- Electromechanical Components
- Electronic Modules
- Fiber Optics
- Filters
- Identification Labeling Products
- Passive Components
- Power Sources
- RF & Microwave Products
- Tooling Products
- Touch Screen Displays
- Tubing, Molded and Harnessing Products
- Wire, Cable and Cable Assemblies
- List all Product Types

- [Aerospace & Defense](#)
- [Appliance](#)
- [Automotive](#)
- [Communications](#)
- [Computer & Consumer Electronics](#)
- [Industrial & Commercial](#)
- [Instrumentation & Medical Equipment](#)


[By Brand](#)

[A to Z](#)

- [Documentation](#)
 - [Find Documents & Drawings](#)
 - [Find CAD Models](#)
 - [SPICE/Electrical Models](#)
 - [NAFTA Certificate of Origin](#)
 - [White Papers](#)
- [Resources](#)
 - [RoHS Compliance & Alternates](#)
 - [Cross Reference Products](#)
 - [Compare Multiple Products](#)
 - [Check Distributor Inventory](#)
 - [Find Authorized Distributors](#)
- [My Account](#)
 - [Sign In](#)
 - [Register](#)
- [Customer Support](#)
 - [Support](#)
 - [RoHS Support Center](#)
 - [Glossary of Terms](#)
 - [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [Protection Products](#) > [Product Feature Selector](#) > Product Details

D-181-2222-90/9 Product Details



D-181-2222-90/9

Raychem Part Number: 179544-000

 [Active](#)

Shield Terminators

 [Always ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Sealing = Splash Resistant
- Cable Temperature Rating = 125 °C
- Jacket Outer Diameter = 1.90 - 4.30 mm
- Shield O.D. (Min.) = 1.50 - 3.60 mm
- With Preinstalled Lead

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [Coaxial Solder Sleeve Device with Pre-installed Lead](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Mechanical Attachment:

- Inside Diameter (mm [in]) = 4.50 [0.180]

Body Related Features:

- [Jacket Outer Diameter \(mm \[in\]\)](#) = 1.90 – 4.30 [0.075 – 0.170]

Housing Related Features:

- [Sealing](#) = Splash Resistant
- [Shield O.D. \(Min.\) \(mm \[in\]\)](#) = 1.50 – 3.60 [0.060 – 0.140]
- [Preinstalled Lead](#) = With
- Preinstalled Lead Wire Size (mm² [AWG]) = 0.38 [22]
- MIL or NAS Specification (MIL-S-83519) (NAS 1747) = No
- Length (Max.) (mm [in]) = 22.70 [0.895]

Configuration Related Features:

- Temperature Indication System = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was ELV compliant

Conditions for Usage:

- [Cable Temperature Rating \(°C\)](#) = 125
- Operating Temperature (Max.) (°C) = 150

Other:

- Brand = Raychem

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved