

Thomas&Betts

Catalog Number: Product ID: UPC Number: EAN Number: Status: **D8-PS-D** 7TAI029630R0080 78621089076 05415022340068 A

Non-Insulated Parallel Splice Connector For Wire Range 8 For Circular Mil Range 13,100-20,800, Length 0.375, Diameter 0.26, Metallic

- Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands.
- Feature an intelligent constructable part number for quick identification of the wire range.
- Application Tools: ERG4005, WT115A, TBM8750M1, TBM8750BSCR

North American Specifications (UNSPSC)		
UNSPSC	39121449 Wire or cable compression splice	
IGCC	4669 Wire or cable compression splice	
Brand Name	Sta-Kon	
Туре	Splice Connector	
Special Features	Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands. Feature an intelligent constructable part number for quick identification of the wire range.	
Standard	UL E9809	
Material	Copper	
Finish	Tin Plated	
Color	Metallic	
Voltage Rating	600 V	

European Specifications (ETIM)

ETIM	EC001059 Crimp splices for copper conductor
Material	Copper
Surface protection	Tinned
Insulation	None
Type of connection	End connector

Раскаді	ng
---------	----

Inner Quantity	500
Inner Dimensions (inches)	5x4.5x3
Outer Quantity	5000
Outer Dimensions (inches)	24x11x4.25
Weight Uom	0.38 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet

WSD-000229

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

Actual