

Customer Information Sheet

DRAWING No.: D95XXX-XX

SHEET 2 OF 2

IF IN DOUBT - ASK

©

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

PART No.	No. OF CONTACTS	STYLE	DIM 'A'	DIM 'B'	DIM 'C'	DIM 'D'
D95006-XX	6	1	7.60	5.08	7.62	10.02
D95008-XX	8	1	10.10	7.62	7.62	10.02
D95014-XX	14	1	17.70	15.24	7.62	10.02
D95016-XX	16	1	20.30	17.78	7.62	10.02
D95018-XX	18	2	22.80	20.32	7.62	10.02
D95020-XX	20	2	25.30	22.86	7.62	10.02
D95022-XX	22	2	27.80	25.40	7.62	10.02
D95A22-XX	22	2	27.80	25.40	10.16	12.60
D95024-XX	24	2	30.40	27.94	15.24	17.64
D95A24-XX	24	2	30.40	27.94	7.62	10.02
D95B24-XX	24	2	30.40	27.94	10.16	12.60
D95028-XX	28	2	35.50	33.02	15.24	17.64
D95032-XX	32	2	40.60	38.10	15.24	17.64
D95040-XX	40	3	50.80	48.26	15.24	17.64
D95A48-XX	48	3	60.90	58.42	15.24	17.64
D95064-XX	64	4	81.20	78.74	22.86	25.40

SPECIFICATIONS:

MATERIALS:

MOULDING (D95XXX-01) = GLASS-FILLED PBT, UL94V-0, BLACK
 MOULDING (D95XXX-42) = GLASS-FILLED PCT, UL94V-0, BLACK
 CONTACT SHELL = BRASS
 CONTACT CLIP = BERYLLIUM COPPER

FINISH:

CLIP = 0.75µ GOLD
 SHELL (D95XXX-01) = 5µ TIN/LEAD
 SHELL (D95XXX-42) = 5µ 100% TIN

ELECTRICAL:


CURRENT RATING = 1 AMP
 VOLTAGE RATING = 100V AC, 150V DC
 CONTACT RESISTANCE = 10 MILLIOHMS MAX
 INSULATION RESISTANCE = 10,000 MEGOHMS MIN
 DIELECTRIC STRENGTH = 1,000V AC MIN

ENVIRONMENTAL:


TEMPERATURE = -55°C TO +125°C

MECHANICAL:


DURABILITY = 100 CYCLES MIN
 INSERTION FORCE (Ø0.43mm GAUGE) = 3.0N MAX
 WITHDRAWAL FORCE (Ø0.43mm GAUGE) = 0.5N MIN




STYLE '1'





STYLE '2'



STYLE '3'



STYLE '4'



ORDER CODE:
D95XXX-XX

SERIES CODE —
 SEE TABLE

No. OF CONTACTS —
 SEE TABLE

FINISH —
 01 - TIN/LEAD SHELL, GOLD CLIP
 42 - 100% TIN SHELL, GOLD CLIP

JMB	2	13.12.05	8918
NAME	ISS.	DATE	C/NOTE
APPROVED: <i>[Signature]</i>			
CHECKED: <i>[Signature]</i>			
DRAWN: WJ BOURNE			
CUSTOMER REF.:			
ASSEMBLY DRG:			

NOTES:

1. STYLE REFERS TO NUMBER OF CENTRE BARS ONLY.
2. FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C004XX (LATEST ISSUE).
3. RECOMMENDED HOLE SIZE = Ø0.80mm.
4. RECOMMENDED PC BOARD THICKNESS = 1.4 - 2.00mm
5. RECOMMENDED MATING PIN DIA. = Ø0.40 - 0.56mm
6. MAXIMUM CONTACT DEPTH = 2.40mm.
MAXIMUM PIN LENGTH = 3.65mm.

HARWIN

HARWIN USA
 TEL: 603 893 5376
 FAX: 603 893 5396
 mis@harwin.com

HARWIN Europe (UK)
 TEL: 023 9231 4545
 FAX: 023 9231 4590
 mis@harwin.co.uk

HARWIN Asia
 TEL: +65 6 779 4909
 FAX: +65 6 779 3868
 mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
 X. = ±1mm
 X.X = ±0.25mm
 X.XX = ±0.10mm
 X.XXX = ±0.01mm
 ANGLES = ±5°
 UNLESS STATED

MATERIAL:
 SEE ABOVE

FINISH:
 SEE ABOVE

S/AREA:
 mm²

TITLE: 2.54mm PITCH DIL EXTENDED VERTICAL IC SOCKET ASSEMBLY

DRAWING NUMBER: D95XXX-XX

SHT 2 OF 2