

DCP60 600W Single Output Lab Grade Switching Power Supply

High efficiency switching power supply with low ripple and noise is ideal for demanding laboratory applications. Remotely control power ON/OFF and Voltage/Current output.

Designed for Laboratory use but excellent for bench technicians, engineers, and educational facilities



Features

- 60V/10A output
- Maximum current can be limited to 5A using front panel auxiliary output on the front panel (10A main output is on the back panel)
- Three user-defined Voltage and Current presets
- Dual action rotary encoder control with push knob for fine and coarse tuning

- Remote control for Output Voltage/Current and On/Off
- Complete with power cord

Specifications

Output Voltage	1 to 60V
Output Current	1 to 10A
Basic Accuracy	±(0.2%+3 digits)
Load Voltage Regulation	50mV
Line Voltage Regulation	20mV
Load Current Regulation	100mA
Line Current regulation	50mA
Ripple and Noise	≤5m Vrms, ≤100m Vp-p
Dimensions/ Weight	7.9 x 3.5 x 8.5" (200 x 90 x 215mm)/ 5.7lbs (2.6kgs)

Ordering

Specifications subject to change without notice. Copyright © 2013 FLIR Systems, Inc. All rights reserved including the right of reproduction in whole or in part in any form.

 ϵ

www.extech.com

0 561 8187

