

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips Within Results

 Text Search: 'DMNF2-288-C'

Your search criteria matched only one product, shown below

DMNF2-288-C



- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection

Part Number	DMNF2-288-C
RoHS Compliancy Status	Compliant
Part Description	Metric Female Disconnect, 1.5 – 2.5mm ² wire range, 2.8mm x .8mm tab size, nylon barrel insulated, funnel entry.
Product Type	Disconnects - Metric
Height (mm)	2.0
Length (mm)	18.8
Width (mm)	3.8
Max. Ins.	4.20
Panduit Color Code	Blue
Pricing Description	Metric Female Disconnect, nylon barrel insulated, 1.5 - 2.5mm ² wire range, 2.8 x .8mm tab size, funnel entry
Tab Size (mm)	2.8 x .8
Tool	CT-1551
Wire Range (mm ²)	0.5 - 1.0
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.