

ExStik[®] II DO/pH/Conductivity Kit

User friendly kit economically measures 6 parameters
Including Dissolved Oxygen, pH, Conductivity, TDS, Salinity, and Temperature

Features:

- Convenient DO/pH/Conductivity Kit with all the accessories and carrying case for easy travel
- Designed for water, wastewater, groundwater, aquaculture and fisheries professionals

Kit includes:

- EC500 pH/Conductivity ExStik[®] II meter with combination high accuracy multi-ranging Conductivity sensor for Conductivity, TDS, Salinity, pH and Temperature measurements
- DO600 Dissolved Oxygen ExStik[®] II meter with electrode, replacement membrane cap, and electrolyte
- Meters waterproof to IP57 standard

Accessories included:

- Sample pH buffers - Single use pouches for pH4, pH7, pH10, and rinse solutions
- Weighted base with 2 cups and caps, four 3V CR-2032 batteries and neckstrap with each meter, and carrying case



Patents Pending

Specifications	Range
TDS/Salinity	0 to 99.9ppm (mg/L), 100 to 999ppm (mg/L) 1.0 to 9.99ppt (g/L)
pH	0.00 to 14.00pH
DO (saturation mode)	0 to 200.0%
DO (concentration mode)	0 to 20.00ppm (mg/L)
Temperature (pH, Conductivity)	23 to 194°F (-5 to 90°C)
Temperature (DO)	32 to 122°F (0 to 50°C)
DO (concentration mode)	0 to 20.00ppm (mg/L)
Automatic Temp Compensation	Yes
Max Resolution	DO600: 0.1%, 0.01ppm (mg/L) EC500: 0.1μS, 0.01ppm (mg/L)
Basic Accuracy	DO600: ±2.0%FS, 0.4ppm (mg/L) ±1.8°F/1°C EC500: ±2.0%FS, 0.01pH, ±1.8°F/1°C
Dimensions	9.5 x 6.8 x 2.8" (241 x 173 x 71mm)
Weight	1.56 lbs. (708g)

Ordering Information:

DO610ExStik[®] II DO/pH/Conductivity Kit
EX010Extension Cable, 3ft (1 Meter) with probe weight for ExStik
EX050Extension Cable, 16ft (5 Meters) with probe weight for ExStik

