

Banner's Call for Parts creates a steady workflow and pinpoints critical issues. Learn more.

# DXM1200-B1R1

## ▶ INDUSTRIAL WIRELESS CONTROLLER: DXM SERIES






DXM1200 Controller  
 IP67  
 DX80 ISM 900 MHZ Performance Radio  
 LCD Display  
 Part Number: 801553










## ACCESSORIES TO COMPLETE YOUR SYSTEM

Add all or individual items to your cart. More options available below.

	<p><b>SMBWSQ120</b></p> <p>Bracket Shroud Q120          16 Gauge 304 SS          Hardware Packet 5 X M4 X .7 X 12 PPHMS-SS 5 X M4 ITLW-SS</p> <p>Out of Stock</p>
	<p><b>IVUC-E-406</b></p> <p>Cordset: Ethernet Adaptor          Pico 4-pin to RJ45          Cable length: 2 m (6 ft)</p> <p>In Stock</p>


 Offline (Contact Us)

	<p><b>IVUC-E-415</b></p> <p>Cordset: Ethernet Adaptor Pico 4-pin to RJ45 Cable length: 5 m (15 ft)</p> <p>In Stock</p>
	<p><b>CSB-M1250M1250-T</b></p> <p>Euro-style Quick Disconnect T Splitter Connector 5-Pin Female Trunk Straight 5-Pin Female T Branch (1) 5-Pin Male T Branch(1) Black TPU Splitter Junction</p> <p>In Stock</p>
	<p><b>CSB4-M1251M1250</b></p> <p>Splitter M128M 5- Pin Euro to M12F 5- pin Euro, M12F 5- pin Euro, M12F 5- pin Euro and M12F 5- pin Euro connectors Black PVC 22-5 AWG Trunk cordset, Straight Connectors Trunk: 0.3 m; Branches: 0.0 m</p> <p>In Stock</p>
	<p><b>SXI-LTE-001</b></p> <p>DXM Controller Accessory: Cellular Data Modem Networks: Verizon 4G LTE Cat. 1 USA Only Plugs directly to DXM Main Board without Tools Kit includes Antenna and Connector Cable</p> <p>Limited Stock</p>
	<p><b>PSW-24-1</b></p> <p>DC Power Supply - Wall Mount Input: 100 -240 V ac 50/60 Hz: Multi-blade outlet plug Output: 24 V dc 1A: 2 m (6.5 ft) Euro 4-pin Connector UL Listed Class 2</p> <p>In Stock</p>
	<p><b>SXI-GSM-001</b></p> <p>DXM Controller Accessory: Cellular Data Modem Networks: Worldwide HSPA 3G with 2G GSM Fallback Plugs directly to DXM Main Board without Tools Kit Includes Antenna and Connector Cable</p> <p>Out of Stock</p>

 Offline (Contact Us)


**SPECIFICATIONS**

<b>Housing Style</b>	IP67 Internal Antenna
<b>Power Supply</b>	12-30V dc
<b>Environmental Rating (IP)</b>	IP67
<b>Max Temp Operating Conditions</b>	60
<b>LCD Display</b>	Yes
<b>Min Temp Operating Conditions</b>	-20
<b>Relative Humidity</b>	95%
<b>Point-to-Multipoint Topology</b>	Yes
<b>Point-to-Point Topology</b>	Yes
<b>Star Topology</b>	Yes
<b>Tree Topology</b>	No
<b>Processing Speed (MHz)</b>	300
<b>On-Board Memory (MB)</b>	16
<b>Feature: Hazardous Area</b>	No
<b>Application: Indicator Light</b>	Yes
<b>EtherNet/IP</b>	Yes
<b>Modbus RTU</b>	Yes
<b>Modbus/TCP</b>	Yes
<b>PROFINET</b>	Yes
<b>RS-232</b>	No
<b>RS-485</b>	Yes
<b>Wireless</b>	Yes
<b>Wireless Radio Frequency</b>	900 MHz
<b>1-wire Serial Interface</b>	No

 Offline (Contact Us)

## COMPATIBLE PRODUCTS


### BRACKET

	<p><b>SMBWSQ120</b></p> <p>Bracket Shroud Q120            16 Gauge 304 SS            Hardware Packet 5 X M4 X .7 X 12 PPHMS-SS 5 X M4 ITLW-SS</p>
---	---

### SINGLE-ENDED CORDSETS



	<p><b>MQDC1-506</b></p> <p>Euro-style Quick Disconnect Cable            5 Pin Straight Connector            2 m (6.5 ft) in Length            Chrome plated brass coupling nut</p>
	<p><b>MQDC1-506RA</b></p> <p>Euro-Style Quick Disconnect Cable            5-Pin Right-Angle Connector            2 m (6.5 ft) in Length            Chrome-plated brass coupling nut</p>
	<p><b>MQDC1-530</b></p> <p>Euro-style Quick Disconnect Cable            5 Pin Straight Connector            9 m (30 ft) in Length            Chrome plated brass coupling nut</p>
	<p><b>MQDC1-530RA</b></p> <p>Euro-Style Quick Disconnect Cable            5-Pin Right-Angle Connector            9 m (30 ft) in Length            Chrome-plated brass coupling nut</p>

### SPLITTERS

	<p><b>CSB-M1250M1250-T</b></p> <p>Euro-style Quick Disconnect T Splitter Connector            5-Pin Female Trunk Straight            5-Pin Female T Branch (1)            5-Pin Male T Branch(1)            Black TPU Splitter Junction</p>
---	---

	<p><b>CSB4-M1251M1250</b></p> <p>Splitter M128M 5- Pin Euro to M12F 5- pin Euro, M12F 5- pin Euro, M12F 5- pin Euro and M12F 5- pin Euro connectors</p> <p>Black PVC 22-5 AWG Trunk cordset, Straight Connectors</p> <p>Trunk: 0.3 m; Branches: 0.0 m</p>
---	---

## MISCELLANEOUS

	<p><b>SXI-CATM1ATT-001</b></p> <p>DXM Controller Accessory: Cellular Data Modem</p> <p>Networks: AT&amp;T 4G LTE CAT M1 North America Only</p> <p>Plugs Directly to DXM Main Board Without Tools</p> <p>Kit Includes Antenna and Connector Cable</p>
	<p><b>SXI-CATM1VZW-001</b></p> <p>DXM Controller Accessory: Cellular Data Modem</p> <p>Networks: Verizon 4G LTE CAT M1 USA Only</p> <p>Plugs Directly to DXM Main Board Without Tools</p> <p>Kit Includes Antenna and Connector Cable</p>
	<p><b>SXI-LTE-001</b></p> <p>DXM Controller Accessory: Cellular Data Modem</p> <p>Networks: Verizon 4G LTE Cat. 1 USA Only</p> <p>Plugs directly to DXM Main Board without Tools</p> <p>Kit includes Antenna and Connector Cable</p>
	<p><b>PSD-24-4</b></p> <p>DC Power Supply - Desktop Style</p> <p>Input: 90-264 V ac 50/60 Hz: 1.8 m (6 ft) US Style outlet plug</p> <p>Output: 24 V dc 4 A: 2 m (6.5 ft) Euro 4-pin Connector</p> <p>UL Listed Class 2</p>
	<p><b>PSW-24-1</b></p> <p>DC Power Supply - Wall Mount</p> <p>Input: 100 -240 V ac 50/60 Hz: Multi-blade outlet plug</p> <p>Output: 24 V dc 1A: 2 m (6.5 ft) Euro 4-pin Connector</p> <p>UL Listed Class 2</p>




**SXI-GSM-001**

DXM Controller Accessory: Cellular Data Modem  
Networks: Worldwide HSPA 3G with 2G GSM Fallback  
Plugs directly to DXM Main Board without Tools  
Kit Includes Antenna and Connector Cable



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

 Offline (Contact Us)