






THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

M SERIES RAISED ACTUATOR

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		INITIAL RELEASE	29MAY2017	SK AS



P.C.B. LAYOUT



- EDS
- 04Q
- POSITIONS: 01,02,03,04,05,06, 07,08,09,10,12
- HALOGEN FREE
- ROHS COMPLIANT
- SMT: SG=GULL WING, SN=J STYLE
- PACKAGING: TU=TUBE, TR=TAPE AND REEL
- ACTUATOR: N=RAISED, R=RECESSED
- SEAL: N=NONE, S=TOP SEAL





THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: SHIVAKUMAR S S	TE Connectivity	
DIMENSIONS: mm[INCHES]		CHK: ALEXANDER SHARPE	NAME: END STACKABLE DIP SWITCHES RAISED ACTUATOR	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD: ALEXANDER SHARPE	SIZE: A2	
0 PLC ± -		PRODUCT SPEC	CAGE CODE: 00779	DRAWING NO: C=2319847
1 PLC ± -		APPLICATION SPEC	SCALE: 1:1	SHEET: 1 of 4
2 PLC ± 0.20[.008]		WEIGHT	RESTRICTED TO	REV: A
3 PLC ± -		CUSTOMER DRAWING		
4 PLC ± -				
ANGLES ± -				
FINISH				

2319847

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

J SERIES RAISED ACTUATOR



P.C.B. LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 29MAY2017 SHIVAKUMAR S S		
DIMENSIONS: mm[INCHES]		CHK 12MAY2017 ALEXANDER SHARPE		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 29MAY2017 ALEXANDER SHARPE	NAME	
0 PLC ± -		PRODUCT SPEC	END STACKABLE DIP SWITCHES RAISED ACTUATOR	
1 PLC ± -		APPLICATION SPEC	SIZE	CAGE CODE
2 PLC ± 0.20[.008]		WEIGHT	A2	00779
3 PLC ± -		CUSTOMER DRAWING	SCALE	SHEET
4 PLC ± -			1:1	2 of 4
ANGLES ± -			REV	A
FINISH				

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

NOTES	SERIES	B	A	No OF POSITION	TE DESCRIPTIVE PART NUMBER	TE PART NUMBER
		DIM				
3	J	27.94 [1.100]	30.38 [1.196]	12	EDS12SNNNTR04Q	4-2319847-2
		22.86 [.900]	25.3 [.996]	10	EDS10SNNNTR04Q	4-2319847-1
		20.32 [.800]	22.76 [.896]	09	EDS09SNNNTR04Q	4-2319847-0
		17.78 [.700]	20.22 [.796]	08	EDS08SNNNTR04Q	3-2319847-9
		15.24 [.600]	17.68 [.696]	07	EDS07SNNNTR04Q	3-2319847-8
		12.70 [.500]	15.14 [.596]	06	EDS06SNNNTR04Q	3-2319847-7
		10.16 [.400]	12.60 [.496]	05	EDS05SNNNTR04Q	3-2319847-6
		7.62 [.300]	10.06 [.396]	04	EDS04SNNNTR04Q	3-2319847-5
		5.08 [.200]	7.52 [.296]	03	EDS03SNNNTR04Q	3-2319847-4
	2.54 [.100]	4.98 [.196]	02	EDS02SNNNTR04Q	3-2319847-3	
	M	27.94 [1.100]	30.38 [1.196]	12	EDS12SGNNTR04Q	3-2319847-2
		22.86 [.900]	25.3 [.996]	10	EDS10SGNNTR04Q	3-2319847-1
		20.32 [.800]	22.76 [.896]	09	EDS09SGNNTR04Q	3-2319847-0
		17.78 [.700]	20.22 [.796]	08	EDS08SGNNTR04Q	2-2319847-9
		15.24 [.600]	17.68 [.696]	07	EDS07SGNNTR04Q	2-2319847-8
		12.70 [.500]	15.14 [.596]	06	EDS06SGNNTR04Q	2-2319847-7
		10.16 [.400]	12.60 [.496]	05	EDS05SGNNTR04Q	2-2319847-6
		7.62 [.300]	10.06 [.396]	04	EDS04SGNNTR04Q	2-2319847-5
5.08 [.200]		7.52 [.296]	03	EDS03SGNNTR04Q	2-2319847-4	
2.54 [.100]	4.98 [.196]	02	EDS02SGNNTR04Q	2-2319847-3		
-	2.44 [.096]	01	EDS01SGNNTR04Q	2-2319847-2		
	27.94 [1.100]	30.38 [1.196]	12	EDS12SNNNTU04Q	2-2319847-1	

NOTES	SERIES	B	A	No OF POSITION	TE DESCRIPTIVE PART NUMBER	TE PART NUMBER
		DIM				
2	J	22.86 [.900]	25.3 [.996]	10	EDS10SNNNTU04Q	2-2319847-0
		20.32 [.800]	22.76 [.896]	09	EDS09SNNNTU04Q	1-2319847-9
		17.78 [.700]	20.22 [.796]	08	EDS08SNNNTU04Q	1-2319847-8
		15.24 [.600]	17.68 [.696]	07	EDS07SNNNTU04Q	1-2319847-7
		12.70 [.500]	15.14 [.596]	06	EDS06SNNNTU04Q	1-2319847-6
		10.16 [.400]	12.60 [.496]	05	EDS05SNNNTU04Q	1-2319847-5
		7.62 [.300]	10.06 [.396]	04	EDS04SNNNTU04Q	1-2319847-4
		5.08 [.200]	7.52 [.296]	03	EDS03SNNNTU04Q	1-2319847-3
		2.54 [.100]	4.98 [.196]	02	EDS02SNNNTU04Q	1-2319847-2
	M	27.94 [1.100]	30.38 [1.196]	12	EDS12SGNNTU04Q	1-2319847-1
		22.86 [.900]	25.3 [.996]	10	EDS10SGNNTU04Q	1-2319847-0
		20.32 [.800]	22.76 [.896]	09	EDS09SGNNTU04Q	2319847-9
		17.78 [.700]	20.22 [.796]	08	EDS08SGNNTU04Q	2319847-8
		15.24 [.600]	17.68 [.696]	07	EDS07SGNNTU04Q	2319847-7
		12.70 [.500]	15.14 [.596]	06	EDS06SGNNTU04Q	2319847-6
		10.16 [.400]	12.60 [.496]	05	EDS05SGNNTU04Q	2319847-5
		7.62 [.300]	10.06 [.396]	04	EDS04SGNNTU04Q	2319847-4
		5.08 [.200]	7.52 [.296]	03	EDS03SGNNTU04Q	2319847-3
2.54 [.100]	4.98 [.196]	02	EDS02SGNNTU04Q	2319847-2		
-	2.44 [.096]	01	EDS01SGNNTU04Q	2319847-1		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 29MAY2017 SHIVAKUMAR S S	TE TE Connectivity	
DIMENSIONS: mm[INCHES]		CHK 12MAY2017 ALEXANDER SHARPE		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 29MAY2017 ALEXANDER SHARPE	NAME	
0 PLC ± -		PRODUCT SPEC	END STACKABLE DIP SWITCHES RAISED ACTUATOR	
1 PLC ± -		APPLICATION SPEC	SIZE	CAGE CODE
2 PLC ± 0.20[.008]		WEIGHT	A2	00779
3 PLC ± -		CUSTOMER DRAWING	SCALE	DRAWING NO
4 PLC ± -			1:1	2319847
ANGLES ± -			SHEET	REV
FINISH			3 of 4	A

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
-	-	SEE SHEET 1	-	-


SOLDERING CONDITIONS:

THE CONDITIONS MENTIONED BELOW IS THE TEMPERATURE ON THE CU FOIL OF THE P.C.B SURFACE. DO NOT ALLOW THE SWITCH'S SURFACE TEMPERATURE TO EXCEED 260°C.

MANUAL SOLDERING


SOLDERING TEMPERATURE	MAX. 350°C.
CONTINUOUS SOLDERING TIME	MAX. 5 SECONDS.

REFLOW SOLDERING



HANDLING PRECAUTIONS

- CARE SHOULD BE EXERCISED SO THAT FLUX FROM THE UPPER PART OF THE PRINTED CIRCUIT BOARD DOES NOT ADHERE TO THE SWITCH.
- DON'T CLEAN THE SWITCH BODY EXCEPT WITH TOP TAPE SEALED TYPE, WHICH CAN ONLY SPRAY OF CLEANING METHOD FROM TOP OF S/W.
- ENSURE FLUX DOES NOT RISE ABOVE THE TOP SURFACE OF THE PCB.



SPECIFICATIONS:

MATERIALS:

BASE: PA (HIGH-TEMP. NYLON) UL94V-0
 COVER: PA (HIGH-TEMP. NYLON) UL94V-0
 ACTUATOR: LCP UL94V-0
 CONTACT: COPPER ALLOY, GOLD (in contact area)
 OVER NICKEL PLATE
 TERMINAL: BRASS ALLOY, GOLD PLATE
 TAPE: POLYAMIDE.

ELECTRICAL:

CONTACT RATING: NON-SWITCHING 100mA @ 50 VDC.
 SWITCHING: 25mA @ 24 VDC.
 INITIAL CONTACT RESISTANCE: 100mΩ MAX. @ 2 VDC. 10mA.
 INSULATION RESISTANCE: 100 MEGOHMS MIN. @ 500 VDC,
 1 MINUTE +/- 5 SECONDS.
 DIELECTRIC STRENGTH: 500 VAC (50 OR 60 HZ), 1 MINUTE.
 DURABILITY: 2,000 CYCLES.
 CAPACITANCE: 5 pF MAX @ 1 MHz +/- 10 KHz.

MECHANICAL:

OPERATING FORCE: 1000gf MAX.

ENVIRONMENTAL:

OPERATING TEMPERATURE: -20°C TO +85°C.
 STORAGE TEMPERATURE: -40°C TO +85°C.
 SOLDER HEAT RESISTANCE PER 109-201, CONDITION B.
 SOLDERABILITY PER JIS C 0050 & JIS C 0053.

NOTES:

1 ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27 JAN 2003 (ROHS).



TUBE PACKAGING.



TAPE AND REEL PACKAGING.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 29MAY2017 SHIVAKUMAR S S		
DIMENSIONS: mm[INCHES]		CHK 12MAY2017 ALEXANDER SHARPE		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 29MAY2017 ALEXANDER SHARPE	NAME	
0 PLC ± -		PRODUCT SPEC	END STACKABLE DIP SWITCHES RAISED ACTUATOR	
1 PLC ± -		APPLICATION SPEC	SIZE	RESTRICTED TO
2 PLC ± 0.20[.008]		WEIGHT	A2	-
3 PLC ± -		CUSTOMER DRAWING	CAGE CODE	DRAWING NO
4 PLC ± -		SCALE	00779	2319847
ANGLES ± -		SCALE 1:1	SHEET 4 OF 4	REV A
FINISH				