



Search by part # or keyword

Products

Industries & Solutions

Resources

TE Store

Sign In



Power Systems > Power Cable Accessories > Raychem Cable Cleats > TE'S RAYCHEM CABLE CLEATS

CC-80-92-SN-M12

CC80-92-SN-M12



Raychem | Raychem CC

TE Internal #: **EF8408-000**

TE Internal Description: **CC80-92-SN-M12**

[All TE'S RAYCHEM CABLE CLEATS \(75\)](#)

Product Availability : **AMERICAS, ANZPAC, ASIA, China, EMEA**

Number of Cables to be Mounted : **1**


Minimum Cable Diameter : **80 mm [3.12 in]**

Maximum Cable Diameter : **92 mm [3.59 in]**

Bolt Hole Centers : **142 mm [5.54 in]**

[Similar Products](#) | [Digital Datasheet](#)

[Compatible Parts & Tooling](#)



We are here to help!

Get in touch with our product experts.

	CHAT WITH US
	EMAIL US
	CALL US

Feedback

Documents	Features	Product Compliance
Product Description	TE's Raychem cable cleats are advanced cable tightening systems for low, medium and high voltage applications. View All TE'S RAYCHEM CABLE CLEATS (75)	
Product Drawings	CC80-92-SN-M12 CC80-92-SN-M12 English	
Datasheets & Catalog Pages	TE's RAYCHEM CABLE CLEATS ENG_DS_EPP-2211_1812.pdf English	
Product Description	TE's Raychem cable cleats are advanced cable tightening systems for low, medium and high voltage applications. View All TE'S RAYCHEM CABLE CLEATS (75)	
Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.		
Product Type Features	Bolt (mm): M12 Type : Cable Clamp	



hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Products with Similar Specs

[View All Similar Products](#)

THIS PRODUCT

TOP RESULTS ?

HARDWARE, GROUNDING & MOUNTING

CC-80-92-SN-M12

CC80-92-SN-M12



Non-Stocked

Product Availability : **AMERICAS, ANZPAC, ASIA, China, EMEA**

Number of Cables to be Mounted : **1**


Minimum Cable Diameter : **80 mm**

Maximum Cable Diameter : **92 mm**

HARDWARE, GROUNDING & MOUNTING

BM9041-000

CC80-92-FM-M12



Non-Stocked

Product Availability : **AMERICAS, ANZPAC, ASIA, China, EMEA**

Number of Cables to be Mounted : **1**


Minimum Cable Diameter : **80 mm**

Maximum Cable Diameter : **92 mm**

HARDWARE, GROUNDING & MOUNTING

BM7015-000

CC80-92-M12-CLAMP-ONLY



Non-Stocked

Product Availability : **AMERICAS, ANZPAC, ASIA, China, EMEA**

Number of Cables to be Mounted : **1**


Minimum Cable Diameter : **80 mm**

Maximum Cable Diameter : **92 mm**

HARDWARE, GROUNDING & MOUNTING

CC-80-92-PL-M12

CC80-92-PL-M12



Non-Stocked

Product Availability : **AMERICAS, ANZPAC, ASIA, China, EMEA**

Number of Cables to be Mounted : **1**

Minimum Cable Diameter : **80 mm**

Maximum Cable Diameter : **92 mm**

Also in the Series | [Raychem CC](#)



Hardware, Grounding
& Mounting (52)

[ABOUT TE CONNECTIVITY](#)

[FOR PARTNERS](#)

[SUPPORT](#)

[CALL US](#)

[LIVE CHAT](#)

[UNITED STATES \(EN\)](#)