



HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY (TE)

X4-1.5-0-SP

Raychem | SWFR X4

EJ1507-000

TE Internal Number: EJ1507-000

EU RoHS Compliant

EU ELV Compliant

Wall Type Single

Resistant To Mechanical Damage

Low Outgassing No

Product Source China

Packaging Method Spool



PRODUCT DRAWING

English

DOCUMENTATION

Product Drawings

SWFR X4 SINGLE WALL HEAT SHRINKABLE TUBING

PDF

English

Catalog Pages/Data Sheets

1-1773894-4_SWFR_Tubing

PDF

English

Very-Thin-Wall, Highly Flame-Retardant, Zero Halogen, Metric-Sized Heat-Shrinkable Tubing

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Wall Type Single

Product Family X4

Electrical Characteristics

Voltage (Max) (kV) .3

Body Features

Shrink Ratio 2:1

Color Black

Flexibility Very Flexible

Material ZEROHAL Polyolefin

Fluid Type Water

Dimensions

Recovered Wall Thickness (Nominal) .25 mm [.01 in]

Expanded Inside Diameter (Min) 1.9 mm [.075 in]

Recovered Inside Diameter (Max) .75 mm [.03 in]

Usage Conditions

Resistant To Mechanical Damage

Recovery Temperature (°C) 90

Operating Temperature Range (°C) -30 – 125

Flammability Flame-Retardant

Shrink Temperature (Min) (°C) 70

Fluid Resistance Moisture/Spray Protection

Product Availability

Applicable Region Global

Packaging Features

Packaging Method Spool

Other

Low Outgassing No

Product Source China

Statement of Compliance

Statement of Compliance

PDF