

Catalog Number: Product ID: UPC Number: EAN Number: Status:

EXN05ASC3

7TCA297180R0230 78621019589 05011949231870 Active

Single Compression Cable Gland, 3/4 Inch NPT Thread, For Use with All Cable Types, Flameproof Ex d and Increased Safety Ex e, Deluge Proof, IP66-68 Rating, Cable Range 6 to 12mm, Nickel Plated Brass

North American Specifications (UNSPSC)	
UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Kopex
Туре	Single Compression Cable Gland
Application	For Use with All Cable to Provide Secure Cable
	Connections Through Knockouts and Threaded En-
	tries
Standard	Approved to EN60079-0, 60079-1, 60079-7, 60079-
	31
Size	3/4 Inch NPT
Conductor Range	6 to 12 Millimeters
Material	Brass
Finish	Nickel Plated
Color	Metallic
Insulation	IP66-68 Rating
Temperature Rating	-40 to 100 Degrees C
Environmental Conditions	Flameproof Ex d

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	3/4 inch
Thread length	21mm
Hexagon angular dimension	31.5mm
Suitable for cable diameter	6.0-12.0mm
Material	Metal
Material quality	Brass
Surface protection	Nickel-plated
Halogen free	Ν
Glass-fibre reinforced	Ν
Degree of protection (IP)	IP68
Shock resistant	Ν
Colour	Natural colour
Bend radius protection/trumpet flare	Ν
With locknut	Ν
Model	Straight
Flat cable coupling	Ν
Strain relief	Ν
Operating temperature	-40-+100°C
Explosion-tested version	Y
For Ex-zone gas	None
For Ex-Zone dust	None
EMC-version	Ν
Packaging	
Inner Quantity	30
Inner Dimensions (inches)	7.09x3.54x3.54



Outer Quantity

120

Outer Dimensions (inches) Weight Uom

3.94x15.75x11.02

0.5 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com