

DC BLOWER 75x75x30mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #24 AWG
 Weight: 61 g



ES **IP** **SF**

Model Number		Voltage (VDC)	Op. Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Additional Function (See Page 3)	Curves
FBD7530B12W2-81	★	12	6.0~13.8	5.50	2.20	23.00	1,500	80	0.96	B	P,M,U,X,Y	①
FBD7530B12W3-81	★	12	6.0~13.8	7.20	4.60	27.40	2,000	110	1.32	B	P,M,U,X,Y	②
FBD7530B12W5-81	★	12	6.0~13.8	8.90	7.50	32.60	2,500	150	1.80	B	P,M,U,X,Y	③
FBD7530B12W7-81	★	12	6.0~13.8	10.70	13.10	37.50	3,000	230	2.76	B	P,M,U,X,Y	④
FBD7530B12W9-81	★	12	6.0~13.8	12.90	17.90	41.80	3,500	360	4.32	B	P,M,U,X,Y	⑤
FBD7530B12W11-81	★	12	6.0~13.8	14.30	23.30	45.90	4,000	510	6.12	B	P,M,U,X,Y	⑥
FBD7530B24W2-81	★	24	12.0~27.6	5.50	2.20	23.00	1,500	70	1.68	B	P,M,U,X,Y	①
FBD7530B24W3-81	★	24	12.0~27.6	7.20	4.60	27.40	2,000	90	2.16	B	P,M,U,X,Y	②
FBD7530B24W5-81	★	24	12.0~27.6	8.90	7.50	32.60	2,500	100	2.40	B	P,M,U,X,Y	③
FBD7530B24W7-81	★	24	12.0~27.6	10.70	13.10	37.50	3,000	140	3.36	B	P,M,U,X,Y	④
FBD7530B24W9-81	★	24	12.0~27.6	12.90	17.90	41.80	3,500	230	5.52	B	P,M,U,X,Y	⑤
FBD7530B24W11-81	★	24	12.0~27.6	14.30	23.30	45.90	4,000	300	7.20	B	P,M,U,X,Y	⑥
FBD7530B48W5-81	★	48	24.0~52.8	8.90	7.50	32.60	2,500	80	3.84	B	P,M,U,X,Y	③
FBD7530B48W7-81	★	48	24.0~52.8	10.70	13.10	37.50	3,000	110	5.28	B	P,M,U,X,Y	④
FBD7530B48W9-81	★	48	24.0~52.8	12.90	17.90	41.80	3,500	150	7.20	B	P,M,U,X,Y	⑤
FBD7530B48W11-81	★	48	24.0~52.8	14.30	23.30	45.90	4,000	220	10.56	B	P,M,U,X,Y	⑥

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

