



FCSM TUBING

HEAVY-WALL, FLAME RETARDANT TUBING (2000V)

KEY FEATURES

- 3:1 shrink ratio
- Sealant-coated tubing
- Flame retardant
- MSHA approved

TE Connectivity's (TE) Raychem FCSM tubing's tough, crosslinked polyolefin construction provides mechanical strength and cut-through resistance equal to, or surpassing, the properties of low-voltage cable jackets.

The FCSM tubing is mainly for use on standard poly or elastomeric insulated or jacketed cables or lead-jacketed cables, which may include aluminum or steel armoring.

TE's FCSM tubing has a 3:1 shrink ratio and an unlimited shelf life when stored under normal conditions.

FCSM tubing is also MSHA approved (No. 07-KA090013-MSHA).

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.



Connectors up to 6 inches: Recommended cut length = connector length + 4 inches. Connectors over 6 inches: Recommended cut length = connector length + 5 inches.

PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)						
Description	2000V Cable Nominal Use Range (AWG/kcmil)	General Use Range	Tube Length*	Standard Ft. (m)/Roll	Pack PCs/Box	Bulk Option Ft. (m)/Roll
In-Line Splice or Terminal Lug Seal (with Sealant)						
FCSM-9/3-1200-S	#14 - #6	0.15 - 0.30 (4 - 8)	48 (1200)	-	25	-
FCSM-19/6-150-S	#6 - #2	0.25 - 0.65 (6 - 17)	6 (150)	-	50	-
FCSM-19/6-1200-S	#6 - #2	0.25 - 0.65 (6 - 17)	48 (1200)	-	25	-
FCSM-28/9-225-S	#2 - 4/0	0.40 - 0.95 (10 - 24)	9 (225)	-	50	-
FCSM-28/9-1200-S	#2 - 4/0	0.40 - 0.95 (10 - 24)	48 (1200)	-	25	-
FCSM-38/12-300-S	1/0 - 350	0.50 - 1.30 (13 - 33)	12 (300)	-	40	-
FCSM-38/12-1200-S	1/0 - 350	0.50 - 1.30 (13 - 33)	48 (1200)	-	10	-
FCSM-51/16-300-S	250 - 500	0.70 - 1.75 (18 - 44)	12 (300)	-	30	-
FCSM-51/16-1200-S	250 - 500	0.70 - 1.75 (18 - 44)	48 (1200)	-	10	-
FCSM-68/22-1200-S	600 - 1000	0.95 - 2.30 (25 - 58)	48 (1200)	-	10	-
FCSM-90/30-1200-S	800 - 1200	1.30 - 3.10 (33 - 79)	48 (1200)	-	5	-
FCSM-120/40-1200-S	1500 - 2500	1.75 - 4.10 (44 - 104)	48 (1200)	-	5	-
FCSM-177/63-600-S		2.75 - 6.05 (70 - 154)	24 (600)	-	6	-
FCSM-177/63-1200-S		2.75 - 6.05 (70 - 154)	48 (1200)	-	5	-
Cable Rejacketing (Without Sealant)						
FCSM-9/3-A/U	#14 - #8	0.15 - 0.30 (4 - 8)	-	100 (30)	-	-
FCSM-19/6-A/U	#6 - #2	0.25 - 0.65 (6 - 17)	-	100 (30)	-	825 (250)
FCSM-28/9-A/U	#2 - 4/0	0.40 - 0.95 (10 - 24)	-	65 (20)	-	495 (150)
FCSM-38/12-A/U	1/0 - 350	0.50 - 1.30 (13 - 33)	-	50(15)	-	395 (120)
FCSM-51/16-A/U	250 - 500	0.70 - 1.75 (18 - 44)	-	40 (12)	-	330 (100)
FCSM-68/22-A/U	600 - 1000	0.95 - 2.30 (25 - 58)	-	80 (24)	-	-
FCSM-90/30-1500/U	800 - 1200	1.30 - 3.10 (33 - 79)	60 (1500)	-	5	-
FCSM-120/40-1500/U	1500 - 2500	1.75 - 4.10 (44 - 104)	60 (1500)	-	5	-
FCSM-177/63-1500/U	-	2.75 - 6.05 (70 - 154)	60 (1500)	-	5	-

* Dimension values provided are typical. Related test reports: EDR-5133, EDR-5134, EDR-5141

ORDERING INFORMATION

1. Select the appropriate catalog number based on typical dimensions for low-voltage insulated cable. Confirm selection with cable dimensions to assure proper sizing.
2. Connectors or lugs not included.
3. If sealing is needed with uncoated FCSM tubing (-/U), order S-1052 separately.
4. Tubing may be field-cut for shorter requirements.
5. Bulk packaging is available for cut-lengths Contact your TE Connectivity representative for additional information.

te.com/energy

© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. E563 10/2014

Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA: +1 800 327 6996
 France: +33 380 583 200
 UK: +44 0870 870 7500
 Germany: +49 896 089 903
 Spain: +34 916 630 400
 Benelux: +32 16 351 731
 Canada: +1 (905) 475-6222
 Mexico: +52 (0) 55-1106-0800
 Latin/S. America: +54 (0) 11-4733-2200
 China: +86 (0) 400-820-6015