

DC AXIAL FAN 40x40x28mm (Stator Outlet Blade)



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 47 g



ES **IP** **SF**

- High Airflow
- Extremely High Static Pressure

Model Number		Voltage (VDC)	Op. Voltage (VDC)	AirFlow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Additional Function (See Page 3)	Curves
FD4028B12W3-85	★	12	6.0~13.8	19.30	38.10	51.70	14,600	460	5.52	B	P,M,U,X,Y	①
FD4028B12W5-85	★	12	6.0~13.8	24.20	55.80	55.70	17,600	650	7.80	B	P,M,U,X,Y	②
FD4028B12W7-85	★	12	6.0~13.8	26.80	70.90	58.60	20,000	810	9.72	B	P,M,U,X,Y	③

● If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

