

DC AXIAL FAN 60x60x38mm (Stator Outlet Blade)



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #24 AWG
 Weight: 95 g



ES **IP** **SF**

- High Airflow
- High Static Pressure

Model Number		Voltage (VDC)	Op. Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Additional Function (See Page 3)	Curves
FD6038B12W3-81	★	12	8.0~13.8	34.50	8.30	52.50	5,000	260	3.12	B	P,U,X,Y	①
FD6038B12W5-81	★	12	8.0~13.8	39.70	11.60	57.00	6,000	360	4.32	B	P,U,X,	②
FD6038B12W7-81	★	12	8.0~13.8	44.70	15.50	60.50	7,000	530	6.36	B	P,U,X,	③
FD6038B24W3-81	★	24	18.0~27.6	34.50	8.30	52.50	5,000	170	4.08	B	P,U,X,Y	①
FD6038B24W5-81	★	24	18.0~27.6	39.70	11.60	57.00	6,000	200	4.80	B	P,U,X,	②
FD6038B24W7-81	★	24	18.0~27.6	44.70	15.50	60.50	7,000	320	7.68	B	P,U,X,	③
FD6038B24W9-81	★	24	18.0~27.6	50.60	18.00	63.10	8,000	390	9.36	B	P,U,X,	④
FD6038B48W3-81	★※	48	30.0~52.8	34.50	8.30	52.50	5,000	80	3.84	B	P,U,X,	①
FD6038B48W5-81	★※	48	30.0~52.8	39.70	11.60	57.00	6,000	110	5.28	B	P,U,X,	②
FD6038B48W7-81	★※	48	30.0~52.8	44.70	15.50	60.50	7,000	160	7.68	B	P,U,X,	③

- If model depicts "★", auto restart protection function built in.
- If model depicts "※", UL and TUV approvals can be implemented upon request.

Specifications are subject to change without notice

