

# CB & AUTOMOTIVE ACCESSORIES

## COMMUNICATION DYNAMIC MICROPHONE for CB and Amateur Applications

Everyone can now enjoy a microphone with superior specifications at a moderate price. Features four (4) conductors, (1 shielded), in a 6-ft. coiled cable designed for relay or electronic switching in transmitters, transceivers and PA amplifiers. Full size, press-to-talk switch extends over half the length of this hand-held mike. High impact shockproof case is attractively styled in matte finish mid-night black. Supplied with rear hang-button.

**Specifications:**  
**Directivity:** Omni - Directional  
**Sensitivity:** -72dB ± 4db at 1KHz  
**Frequency Response:** 200Hz - 5KHz



No. CM43A

## S.W.R. Bridge and Field Strength Meter

Perfect dual-purpose meter for checking SWR measurements, as well as reading the field strength in both mobile and home station rigs. Can monitor transmitter outputs in the circuit continuously.



**Specifications:**  
**SWR:** 1:1 to 1:3  
**RF Power:** 0.5-10W and 0.5-100W Switchable  
**Accuracy:** SWR: +5% Power: +10%  
**Impedance:** 52 ohms  
**Meter Sensitivity:** 200 u A  
**Freq. Range:** 1.7 to 150 MHz  
**Size:** 5-3/4"H x 2-1/4"D x 1-15/16"

No. FS45

Attractive black metal cabinet supplied with detachable antenna, and set of instructions.

## Polarized Automotive Power Cord

**No. TC3616**  
 5 ft. Polarized 3-pin connector red lead contains fuse holder and 2 amp fuse 18 Ga. leads.



## Automotive Power Cord No. TC3640

5 ft.; 16 Ga. red and black leads with fuse holder in-line in red lead with 10 amp fuse. Both ends stripped.



## In-Line Fuse Holder for Blade Type Fuses

**No. FH101**  
 • Material - Bakelite  
 • Max. Rating: 250VAC/30A  
 • Color - Black



## FUSE HOLDER (Screw Type Cap)



**No. 526** - For 3 AG Type Fuse (1/4" x 1-1/4")  
**No. 525** - For GMA Type Fuse (5mm x 20mm)

## Fuse Mounting Bases

**No. H108A** - Single Fuse  
**No. H108B** - Double Fuse



Will accommodate the 3AG cartridge type auto fuse. Clips are made of spring brass, and mounting board is made of 1/8" XP laminated phenolic insulating material.

## MICROPHONE HANG-UP HOLDER with mounting hardware

Stainless Steel



**No. H200SS**  
**No. H200SSB** bulk packed


## Screw Cap Fuse Holder No. FH55

**No. FH55B** - bulk packaged  
 Rating 15A @ 250VAC  
 Holds 1/4" x 1-1/4" fuses. Can be used in panels up to 1/4" thick. Mounts in 19/32" hole. Overall length of holder 2", behind panel 1-3/8".



## In-Line Fuse Holder

**No. FH65**  
**No. FH65B** - bulk packaged  
 Holds 1/4" x 1-1/4" fuses. Spring loaded, twist lock design. Plastic housing provides full insulation. 10" heavy duty #18 gauge stranded insulated wire at each end.



## REPLACEMENT SCREWS for CB's, PA's, Car Mounts, etc.



**No. K40** Size 4 mm  
**No. K50** Size 5 mm  
**No. K60** Size 6 mm

For connecting mounting brackets to metal cases. Made of machined brass with a heavy nickel plated finish. Length of threaded portion is 3/8". Packed two per package.

Add suffix "B" to part number for bulk pack.

## Heavy Duty In-Line Fuse Holder 10A @ 250V AC

**No. 506** - for 3AG type fuse (1/4" x 1-1/4")  
**No. 507** - for GMA type fuse (5.0mm x 20mm)



## SMA TO UHF HT ADAPTOR CABLE

For hand-held Ham or Business Transceivers (HT) with SMA antenna connectors; adapts the antenna connection to a UHF female for connection to mobile or base antennas with a PL-259 termination. The cable is 16" long miniature 50 ohm coaxial cable (RG174/U). Using an adaptor cable will help to reduce strain on the radio's SMA antenna jack.



No. CA740