


- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 60 VAC/75 VDC, 2 A



| Housing Style | Female Part Number | Male Part Number | Features | Pinout |
|--|--------------------|------------------|---|---|
| <p>FKFD ..</p> <p>Typical panel cutout is 15.3 x 14 mm.</p> | FKFD 8-* | FSFD 8-* | 8x24 AWG, 105°C, mates with 8-pin cordsets, UL Recognized, CSA Approved | <p>Female</p> <p>Male</p> |
| | FKFD 8-*/S1505 | FSFD 8-*/S1505 | 8x26 AWG, 105°C, mates with 8-pin cordsets | <p>Female</p> <p>Male</p> |
| | FKFD 10-* | FSFD 10-* | 10x24 AWG, 105°C, mates with 10-pin cordsets | <p>Female</p> <p>Male</p> |
| | FKFD 12-* | FSFD 12-* | 12x24 AWG, 105°C, mates with 12-pin cordsets | <p>Female</p> <p>Male</p> |

Receptacles

* Length in meters. Standard lead length is 0.5 meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FSFD.."; "FSFDV.." indicates stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.