



PRODUCT-DETAILS

# FLB0530

## LT-PVC FLEX CONDUIT 25MM 30M BLK



### General Information

Extended Product Type	FLB0530
Product ID	7TCA297020R0104
EAN	5011949202658
Catalog Description	LT-PVC FLEX CONDUIT 25MM 30M BLK
Long Description	Liquid Tight, Medium Flexibility Conduit, Nominal Conduit Size 25mm, 3/4 Inch US Trade Size, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 30 Meters, Galvanised Steel Core, String Packing, PVC Covering, Black

### Ordering

EAN	5011949202658
Customs Tariff Number	8307106000

### Dimensions

Product Net Weight	34.17 lb 15.497 kg
--------------------	-----------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

---

### Additional Information

Application	Indoors/Outdoors, Marine, Buildings, Infrastructure
Brand / Label	Kopex
Color	Black
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with String Packing and PVC Covering
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	flex metal conduit
Product Type	Liquid Tight Metallic Conduit
Radius	110 mm
Standards	BSI Kitemark KM-90009, Low Voltage Directive
UPC	786210276526

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	FLB0530
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	FLB0530

---

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

