

Type FPK-R
UL Class CC – Current Limiting
Branch Circuit Protection
Fast Acting - 13/32”x 1-1/2”



www.optifuse.com

(619) 593-5050

For use as branch circuit protection in general purpose and lighting applications. This fuse provides high current limiting capabilities and a rejection style ferrule.

Electrical:

600VAC - 100mA - 30A
 600VDC - 100mA - 30A

Interrupt Ratings:


200,000A @ 600VAC (100mA-30A)
 100,000A @ 600VDC (100mA-30A)

Agency Standards and Listings:



UL Listed to Standard 248-4 File E2137
 CSA Certified Standard C22.2 No. 248.4
 DC Listed to UL Standard 248

Mechanical Dimensions:



Part Number	Ampere Rating
FPK-R-100mA	100mA
FPK-R-125mA	125mA
FPK-R-200mA	200mA
FPK-R-250mA	250mA
FPK-R-300mA	300mA
FPK-R-500mA	500mA
FPK-R-750mA	750mA
FPK-R-1A	1A
FPK-R-1.25A	1.25A
FPK-R-1.5A	1.5A
FPK-R-2A	2A
FPK-R-2.5A	2.5A
FPK-R-3A	3A
FPK-R-3.5A	3.5A
FPK-R-4A	4A
FPK-R-5A	5A
FPK-R-6A	6A
FPK-R-7A	7A
FPK-R-8A	8A
FPK-R-9A	9A
FPK-R-10A	10A
FPK-R-12A	12A
FPK-R-15A	15A
FPK-R-20A	20A
FPK-R-25A	25A
FPK-R-30A	30A

Warning:



-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.

-Avoid contact of fuse with chemical solvent. Prolonged contact may damage the device performance.


Type FPK-R
UL Class CC – Current Limiting
Branch Circuit Protection
Fast Acting - 13/32”x 1-1/2”




www.optifuse.com

(619) 593-5050

Time Current Curve Graph



Peak Let-Thru Current Graph



Note: All specifications subject to change without notice.