



+ RELAYS, CONTACTORS & SWITCHES

TACTILE SWITCHES



✓ Active

TE CONNECTIVITY (TE)

## FSM1JH=6MM TACT SWITCH, HT W/ESD

Alcoswitch | Alcoswitch Tactile FSM J

1825955-2

TE Internal Number: 1825955-2

Alias ID: FSM1JH

EU RoHS Compliant

EU ELV Compliant

**Actuator Style** Round

**Operating Function** NO

**Contact Base Material** Copper Alloy

**Contact Plating** Silver

**Dust Proof** No

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

### DOCUMENTATION

Product Drawings

#### TACT SWITCH

PDF

English

CAD Files

#### 3D PDF

PDF

3D

#### Customer View Model

2D\_DXF.ZIP

English

## Customer View Model

3D\_IGS.ZIP

English

## Customer View Model

3D\_STP.ZIP

English

---

Product Environmental Compliance

TE Material Declaration

## MD\_1825955-2\_02192014745\_dmtec

PDF

English

---

## FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

---

### Product Type Features

**Illuminated** With

**Leg Style** Kinked

**Actuator Style** Round

**Dust Proof** No

**Product Type** Switch

---

### Configuration Features

**Snap Action** Without

**Tactile** Yes

**Operating Function** NO

**Support Bracket** Without

**Number of Actuators** 1

**Ganged** With

**ESD Grounding Terminal** With

**Tactile Feel** With

---

### Body Features

**Bushing Style** Unthreaded

**Case Material** Polyamide

**Actuator Color** Brown

**Actuator Force** 100 g [ 3.53 oz ]

**Case Color** Black

**Cover Material** Steel

**Actuator Material** PBT

**Actuator Profile** Extended

---

### Contact Features

**Contact Base Material** Copper Alloy

**Contact Plating** Silver

**Contact Current Rating (mA)** 50

## Termination Features

**Termination Type** Printed Circuit Board

---

## Mechanical Attachment

**Mounting Type** Through Hole

**Mounting Angle** Vertical

---

## Housing Features

**Low Profile** With

**Process Sealed** No

---

## Dimensions

**Switch Height** 4.3 mm [ .169 in ]

**Button Width** 3.5 mm [ .138 in ]

**Actuator Length** .7 mm [ .028 in ]

---

## Usage Conditions

**Temperature Rating (°C)** High

---

## Packaging Features

**Packaging Method** Loose Piece

---

## Other

**Comment** (On) indicates momentary position.

---

## PRODUCT COMPLIANCE



### Statement of Compliance

#### **Statement of Compliance**

PDF

---