



Panel Interface Connectors

Popular PIC Models



Standard Metal Housing | UL Type 4, 4X, 12 | IP65 Rating

Part Number	Description	Faceview	Part Number	Description	Faceview
DP-DB9-RJ45-R-32	Duplex Receptacle 9 Pin D-Sub RJ45 3 AMP Reset Size 32 Housing		DP-2RJ45-R-32	Duplex Receptacle 2- RJ45 3 AMP Reset Size 32 Housing	
GF-RJ45-5R-32	GFCI Receptacle RJ45 5 AMP Reset Size 32 Housing		DP1-2DB9-RJ45-R-32	Single Outlet 2 x 9 Pin D-Subs RJ45 3 AMP Reset Size 32 Housing	
DP1-DB9-USB-*-24LS	Single Outlet 9 Pin D-Subs USB Form A Female with Cable to USB Form A Male Size 24 Housing		GF-RJ45-10R-32	GFCI Receptacle RJ45 10 AMP Reset Size 32 Housing	
DP1-RJ45-R-16LS	Single Outlet 3 AMP Reset RJ45 Size 16 Housing		GF-2RJ45-R-32	GFCI Receptacle 2 x RJ45 3 AMP Reset Size 32 Housing	
DP-DB9-PC9-RJ45-R-32	Duplex Receptacle 9 Pin D-Sub to Terminal Block RJ45 3 AMP Reset Size 32 Housing		DP1-RJ45-10LS	Single Outlet RJ45 Size 10 Housing	
DP1-2RJ45-24LS	Single Outlet 2 x RJ45 Size 24 Housing		RJ45-2USB-*-16LS	RJ45 2 x USB Form A Female with Cable to USB Form A Male Size 16 Housing	
DB09-RJ45-10LS	9 Pin D-Sub RJ45 Size 10 Housing		DP-R-32	Duplex Receptacle 3 AMP Reset Size 32 Housing	
DP-R-TS	Duplex Receptacle 3 AMP Reset DIN Rail Mounting		GF-15R-32	GFCI Receptacle 15 AMP Reset Size 32 Housing	
GF-DB15-R-32	GFCI Receptacle 15 Pin D-Sub 3 AMP Reset Size 32 Housing		DP-RJ45-5R-32	Duplex Receptacle RJ45 5 AMP Reset Size 32 Housing	

* Length in feet. Standard cable lengths are 3,6 & 10 feet. Consult factory for other lengths.

Panel Interface Connectors

