



Panel Interface Connectors

Popular PIC Models



Standard Metal Housing | UL Type 4, 4X, 12 | IP65 Rating

Part Number	Description	Faceview	Part Number	Description	Faceview
GF-RJ45-R-32	GFCI Receptacle RJ45 3 AMP Reset Size 32 Housing		GF-DB9-RJ45-R-32	GFCI Receptacle 9 Pin D-Sub RJ45 3 AMP Reset Size 32 Housing	
DP1-RJ45-16LS	Single Outlet RJ45 Size 16 Housing		DB09-06LS	9 Pin D-Sub Size 6 Housing	
DP-RJ45-R-32	Duplex Receptacle RJ45 3 AMP Reset Size 32 Housing		DP1-DB9-RJ45-16LS	Single Outlet 9 Pin D-Sub RJ45 Size 16 Housing	
DP1-RJ45-R-24LS	Single Outlet RJ45 3 AMP Reset Size 24 Housing		EP-RJ45-R-32	European Receptacle RJ45 3 AMP Reset Size 32 Housing	
D-USB-*06LS	USB Form A Female with Cable to USB Form A Male Size 6 Housing		RJ45-CVKIT	Ethernet Kit RJ45 Size 6 Housing (Hood Incl.)	
GF-2-48LS	2 x GFCI Receptacle Size 48 Housing		DP-USB-RJ45-32	Duplex Receptacle 2xUSB A Connections RJ45 Size 32 Housing	
GF-USB-RJ45-32	GFCI Receptacle 2xUSB A connections RJ45 Size 32 Housing		GF-DB15-RJ45-USB-BFAF-32	GFCI Receptacle 15 Pin D-Sub RJ45 USB Form B Female to Form A Female Size 32 Housing	
GF-RJ45-32	GFCI Receptacle RJ45 Size 32 Housing		RJ45-2-10LS	2- RJ45 Size 10 Housing	
RJ45-06LS	RJ45 Size 6 Housing		DP-3USB-AFAF-32	Duplex Receptacle 3 x USB A Female to Male Connector Size 32 Housing	

* Length in feet. Standard cable lengths are 3,6 & 10 feet. Consult factory for other lengths.

PICs with International outlets are non-UL.