

Commercial Specification Grade GFCI Duplex Receptacles



Description	Color	Catalog Numbers	
Flush thermoplastic face, back & side wired, multiple drive screws.	Brown	GFR5252A	GFR5352A
	Ivory	GFR5252IA	GFR5352IA
	Gray	GFR5252GYA	GFR5352GYA
	White	GFR5252WA	GFR5352WA
	Black	GFR5252BKA	GFR5352BKA
	Office White	GFR5252OWA	GFR5352OWA
	Red	GFR5252RA	GFR5352RA



Faceless GFCI

Description	Color	Catalog Numbers	
Faceless, back and side wired multiple drive screws	Brown	-	GFR5350
	Ivory	-	GFR5350I
	White	-	GFR5350W
	Black	-	GFR5350BK

Commercial Hospital Grade GFCI Duplex Receptacles

Description	Color	Catalog Numbers	
Flush nylon face, back & side wired, multiple drive screws.	Brown	GF8200H	GF8300H
	Ivory	GF8200HI	GF8200HI
	Gray	GF8200HGY	GF8300HGY
	Red	GF8200R	GF8300HR
	White	GF8200HW	GF8300HW
	Office White	GF8200HOW	GF8300HOW

Notes: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles listed above include a matching nylon wall plate.



Industrial Heavy Duty Specification Grade GFCI Duplex Receptacles



Description	Color	Catalog Numbers	
Flush nylon face, side wired, multiple drive screws.	Brown	GF5262A	GF5362A
	Ivory	GF5262IA	GF5362IA
	Gray	GF5262GYA	GF5362GYA
	Red	GF5262RA	GF5362RA
	White	GF5262WA	GF5362WA



Heavy Duty Hospital Grade GFCI Duplex Receptacles

Description	Color	Catalog Numbers	
Flush nylon face, side wired, multiple drive screws.	Brown	GF8200A	GF8300A
	Ivory	GF8200IA	GF8300IA
	Gray	GF8200GYA	GF8300GYA
	Red	GF8200RA	GF8300RA
	White	GF8200WA	GF8300WA



Specifications

Trip Level	4 to 6 mA.
Trip Time	.025 sec. nominal.
Frequency	60Hz
Voltage	120V AC +10% - 15%
Maximum Interrupting Capacity	2000A
Operating Temperature	-35° C to +66° C or -30° F to +150° F
Maximum Humidity	95%
Listings & Standards	Meets 2003 UL 943 for GFCIs, UL 943 Class A for GFCIs UL File E41978. CSA Certified.
Codes	Meets all 2002 NEC requirements



Wiring Device-Kellems