

Cable gland - G-INS-M63-E68N-NNES-S - 1424531


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, External cable diameter 37 mm ... 53 mm, Shielding: No, Connecting thread: M63, Color: silver



Key Commercial Data

Packing unit	1
GTIN	 4 055626 374369
GTIN	4055626374369
Custom tariff number	39269097

Technical data

Dimensions

Length	60 mm
Wrench size, union nut	75 mm
Wrench size, support	75 mm
Hexagon angular dimension	70 mm
Length of the connecting thread	10 mm
Feed-through hole diameter	63.1 mm ... 63.3 mm
External cable diameter	37 mm ... 53 mm

Ambient conditions

Degree of protection	IP69
	IP68 (5 bar, 30 min.)
	IP66
Ambient temperature (operation)	-20 °C ... 100 °C (static)

Cable gland - G-INS-M63-E68N-NNES-S - 1424531


Technical data

General

No. of conductors	1
Cable gland material	Nickel-plated brass
Material, insert	Polyamide 6
Cable seal material	Neoprene
Shielded	No
Thread type on connection side	M63
Thread pitch	1.5 mm
Torque	25 Nm (Union nut) 25 Nm (Support)
Color	silver
Impact category	7
Execution of the strain relief	A
Assembly instructions	1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque

Drawings

Dimensional drawing



Dimensional drawing

Approvals

Approvals

Approvals

EAC

Ex Approvals

Cable gland - G-INS-M63-E68N-NNES-S - 1424531

Approvals

Approval details

EAC		EAC-Zulassung
-----	-----------------------------------------------------------------------------------	---------------
