Product data sheet Characteristics

GS1AE2

TeSys GS - shaft extension - 320 mm - 30...400 A

Product availability: Non-Stock - Not normally stocked in distribution facility



Price**: 20.30 USD

GS1AE2 has not been replaced. Please contact your customer care center for more information.



Main

Range	TeSys
Product or component type	Shaft extension
Device short name	GS1AE
Accessory / separate part category	Locking accessory
Product compatibility	GS

Complementary

		:
		-
		9
Main		
Range	TeSys	
Product or component type	Shaft extension	-
Device short name	GS1AE	
Accessory / separate part category	Locking accessory	
Product compatibility	GS	
Camanlamantam		
Complementary	400.4	
Switch rated current	400 A 160 A	
	50 A	:
	63 A	
	125 A	7
	200 A	-
	100 A	
	60 A	<u> </u>
	250 A	:
	315 A	
Type of operating handle	External	
Mounting location	Front	
Length	12.60 in (320 mm)	
Shaft cross section	10 x 10 mm	
Net weight	0.53 lb(US) (0.24 kg)	
Ordering and chinning details		
Ordering and shipping details	22040 IFO DICCONNECT CC4 LI/2	
Category	22640 - IEC DISCONNECT-GS1,LK3	
Discount Schedule	l11	
GTIN	00785901353591	
Package weight(Lbs)	0.25 kg (0.56 lb(US))	
Returnability	No	
5 17 0010		

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3	<u>ta</u> : <u>S</u> :
Discount Schedule	l11	
GTIN	00785901353591	
Package weight(Lbs)	0.25 kg (0.56 lb(US))	
Returnability	No	

, ,	FR	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to www.p65warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

18 months

Warranty