



## Rigid/IMC Conduit Fittings

**T&B Catalog Number:**

H150GR-TB

**UPC Number:**

78621091371

**Status:**

Active

**Description:**

1 1/2 in. Zinc Grounding Hub with thermoplastic insulating throat; sealing ring-Nitrile (BUNA-N). For use with Rigid/IMC Conduit.

### Application

Suitable for hazardous locations use in Class I, Division 2; Class II, Division 1&2; Class III, Division 1 & 2 per NEC 501-4(b); 502-4 (a) and 503-3 (a).

Suitable for hazardous locations use in Class II, Groups E, F, G & Class III locations per CEC 18-202; 18-252; 18-302; 18-352.

### General

Trade Size (inches) 1-1/2

Material Zinc

### Dimension Information

Dimension A (inches) 2 3/4

Dimension B (inches) 1 7/8

Dimension C (inches) 1 1/16

Dimension D (inches) 1/4

Dimension E (inches) 1 17/32

### Specifications

3dmodel Available on Website

### Packaging

Package in Units 10

T&B Sold in UOM Each

T&B Weight Per UOM 0.74 lbs. per 100

### Application Support

Spacing Chart Available on Website

### Certifications

RoHS Compliance No

### Certifications



File Nbr:

E 23018

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com